



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Ave., N.W.
Washington, D.C. 20460

EPA Reg. Number:

2693-237

Date of Issuance:

7/29/19

NOTICE OF PESTICIDE:

Registration
 Reregistration
(under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

Intersmooth 7670

Name and Address of Registrant (include ZIP Code):

Asheley Bowles
PRSA Specialist I
International Paint, LLC
6001 Antoine Drive
Houston, TX 77091

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.


On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:


Eric Miederhoff, Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Date:

7/29/19

2. You are required to comply with the data requirements described in the DCI or EDSP Order identified below:
 - a. 1-H-Pyrrole-3-carbonitrile, 4-bromo-2-(4-chlorophenyl)-5-(4.85% trifluoromethyl) GDCI-119093-1735
 - b. Zinc 2-Pyridinethiol 1-oxide GDCI- GDCI-088002-1483

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI or EDSP Order listed above, you may contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>

3. Be aware that proposed data requirements have been identified in a Work Plan or proposed DCI. For more information on these proposed data requirements, you may contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>
4. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, “EPA Reg. No. 2693-237.”
5. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated 11/02/2018
- Alternate CSF 1 dated 11/02/2018

Page 3 of 3
EPA Reg. No. 2693-237
Decision No. 547397

If you have any questions, please contact Karen M. Leavy by phone at (703)-308-6237 or via email at Leavy.Karen@epa.gov.

Enclosure

<p>A C C E P T E D</p> <p>07/29/2019</p> <p>Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 2693-237</p>
--

INTERSMOOTH 7670
Antifouling Paint
Copper Free Antifouling

Alternative Brand Names (ABNs)

- [INTERSMOOTH 7670 RED]
- [INTERSMOOTH 7670 BROWN]



DANGER/PELIGRO/POISON

KEEP OUT OF REACH OF CHILDREN

See side panel for additional Precautionary Statement

NET CONTENTS: ONE GALLON (3.785 LITERS)

EPA Reg. No.: 2693-XXX
EPA Est. No.: 2693-TX-1

Active Ingredients:	Percentage
1H-Pyrrole-3-carbonitrile, 4-bromo -2- (4-chlorophenyl) -5- (trifluoromethyl)	5.76%
Zinc 2-Pyridinethiol 1-Oxide*	7.54%
Other Ingredients:	<u>86.70%</u>
	100.00%

Contains Petroleum Distillates, xylene or xylene range aromatic solvents
* Zinc Pyrithione

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint, LLC., including surface preparation, proper application, and environmental conditions. Therefore, International Paint, LLC. cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT, LLC. SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint, LLC's option.

International Paint LLC
6001 Antoine Dr.
Houston, TX 77091

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**



DANGER/PELIGRO/POISON

KEEP OUT OF REACH OF CHILDREN

DANGER. Corrosive. Causes irreversible eye damage or skin burns. Fatal if swallowed, or absorbed through skin, or inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wear the proper Personal Protective Equipment as specified below. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before use.

PERSONAL PROTECTIVE STATEMENT (PPE)

Applicators and other handlers must wear:

- Goggle or face shield,
- Coveralls over long-sleeved shirt and long pants,
- Socks and chemical resistant footwear
- Chemical-resistant gloves (such as Barrier Laminate, Butyl nitrile, /Neoprene Rubber, PVC, or Vitron>14 mils)
- Wear a minimum of a NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and combination N1, R, or P filters; OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air purifying respirator with OV cartridges and combination HE filters.

USER SAFETY REQUIREMENTS

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing/PPE immediately if pesticide gets inside, then wash thoroughly and put on clean clothing.

FIRST AID	
If in eyes:	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, and then continue rinsing. • Call a Poison Control Center or doctor for treatment advice.
If on skin or clothing:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
If swallowed:	<ul style="list-style-type: none"> • Immediately call a poison control center or doctor. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give any liquid to the person. • Do not give anything by mouth to an unconscious person.
If inhaled:	<ul style="list-style-type: none"> • Move a person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. • Call a poison control center or doctor for further treatment advice.
<p>General Information: Have the product container or label with you when calling a poison control center or doctor or going for treatment. For non-emergency and general information on product use, etc., information pertaining to this product, call the National Pesticides Information Center (NPIC) at 1-800-858-7378, 8:00-12:00 pm Pacific Time, Monday-Friday, email: npic@ace.orst.edu ; or website: http://npic.orst.edu/ . You may also contact the poison control center 1-800-222-1222 for emergency medical treatment information.</p>	

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS

This material is toxic to fish, aquatic invertebrates, oysters, and shrimp. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: FLAMMABLE. Keep away from heat and open flame.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE: Pesticide product should be kept in securely closed containers. Mixed paint should not be stored under any circumstances. Exposure to air and extreme of temperature should be avoided. Keep out of direct sunlight.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

INTERSMOOTH 7670

PRODUCT DESCRIPTION: A high performance, tributyltin (TBT) free, Copper free, polishing antifouling resistant to algae, barnacles and other marine fouling's. For use in fresh, salt and brackish waters. Prevents coating build-up. At subsequent dry dockings, it is only necessary to top up the system. This antifouling paint is for industrial use and professional application only. Not for sale to the general public.

DIRECTIONS FOR USE **Subset A [Commercial Use]**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

SURFACE PREPARATION AND COMPATIBILITY: Surface preparation directions Must be followed exactly in order to insure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Apply using an airless sprayer. Tip Size 25-30 thou inch, pump ratio of 30:1 or greater. For small areas, brush or roller may be used, but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) or three (3) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary, consult your International representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use INTERNATIONAL GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 4 hours, and before launching is 12 hours at 73°F.

THEORETICAL COVERAGE: 228 square feet per gallon, per coat at 4.0 mils DFT. Consult your International representative for practical application coverages. Practical square foot coverage per gallon, per coat is directly proportional to surface, application techniques and climatic conditions.

APPLICATION SYSTEMS

EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure fresh water wash with a minimum of 3000 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high-pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR CONDITION: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SHIP CONSTRUCTION: Blast entire area to a Near White Metal Standard SSPCSP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

WOOD AND NON-FERROUS SURFACES: Use surface preparation and primers as specified by the Navy.

ALTERNATE DIRECTIONS FOR USE Subset B [Pleasure Craft]

PRODUCT DESCRIPTION: This product is a copper free antifouling that provides excellent protection from shell and weed fouling. It uses Biolux® technology to block slime and Ecomea to ward off barnacles and zebra mussels. The fast-dry formula of this product allows the boat to be painted and launched quickly and its ablative-action reduces paint build up and helps to improve fuel efficiency. This product is available in bright colors and is suitable for use on all boats including fiberglass, aluminum, wood, and steel and can be used in all waters. This product can be brush or roller applied.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL APPLICATION PROCEDURES

For applications by residential (non-commercial) users: Do not apply by airless spray. Do not apply more than one coat of this product within 24 hours. Apply only in outdoor, non-enclosed spaces. Apply at least 2-3 full coats of this product by brush or solvent resistant 3/8" nap roller. **Do not apply thin coats.** Keep in mind that the life of the paint is directly related

to the amount of paint applied. Certain areas of the hull, such as the leading edge of the keel and rudder, the waterline and the bow stem polish faster than other areas. On these areas we suggest an additional coat of paint to ensure that this product does not polish away before other areas of the bottom.

Approximate time it will take to paint your boat

Boat Size	Application Time
14'	40 Minutes per coat
20'	1 Hour 20 Minutes per
30'	2 Hours 40 Minutes per coat

THEORETICAL COVERAGE: 528 ft ² /gal (2 mils dry film thickness)	V.O.C.: Less than 383 grams/liter (3.19 lbs./gallon)
THINNER: SPECIAL THINNER 216	THINNING: Do not exceed 10% by volume

DRY TIMES

Temperature °F (°C)	Touch Dry	Overcoating Time		Immersion Time	
	MIN	MIN	MAX	MIN	MAX
41°F (5°C)	6hrs	12hrs	NA	18 hrs	NA
50°F(10°C)	3hrs	6hrs	NA	9 hrs	NA
73°F (23°C)	2hrs	4 hrs	NA	6hrs	NA
95°F (35°C)	1 h	2hrs	NA	4 hrs	NA

*If the air temperature falls below 41 °F (5°C) during the 4-hour dry time extend the dry times to 24 hours minimum.

COMPATIBILITY: This product is compatible with most other antifouling paints and can be applied after sanding the surface. Tin based copolymers should be removed or sealed with **Primocon YPA984 or TBT Sealer YPA987.**

PREPARATION

BARE FIBERGLASS: It is very important that bare fiberglass be properly prepared to remove the mold release wax completely to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allow to dry. Remove mold release wax using one of the following Interlux products. **Fiberglass Surface Prep YMA60), Fiberglass Solvent Wash 202 or Low VOC Fiberglass Solvent Wash 202V** following the product label instructions. To be certain that all of the contamination has been removed, run water over the surface. If the water beads up or separates, clean again. When the water sheets off, all contamination has been removed.

BARE FIBERGLASS - NO SAND SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using Interlux Watertite filler. Sand and wipe clean. Apply one coat, using one of the following Interlux products **InterProtect® 2000**

or **No Sand Primer YPA200**, following the label instructions for applying the primer and overcoating with antifouling paint.

BARE FIBERGLASS - SANDING SYSTEM: Clean the surface following the preparation procedure above. Repair any surface imperfections using Interlux Watertite filler. Sand and wipe clean: After the surface has been cleaned, sand with ~80-grit sandpaper until a flat, matte finish has been obtained. Wipe off the sanding residue with **Fiberglass Solvent Wash 202**.

BARE WOOD: Sand entire surface thoroughly to a smooth finish with 80-grit sandpaper. Clean off the sanding residue. Prime with **Primocon** thinned 10% with **Special Thinner 216** or thin first coat of this product 10-15% with **Special Thinner 216**. Apply two more coats of this product unthinned, allowing appropriate dry times.

ALUMINUM & UNDERWATER METALS - Please check datasheet for preparation to aluminum and underwater metals or contact Interlux Technical Service at 1-800-468-7589.

PREVIOUSLY PAINTED SURFACES

In Good Condition: Remove all contamination. Sand the entire surface with 80 grit sandpaper; remove sanding residue.

In Poor Condition: Remove all previous coatings using **Interstrip 299E** and proceed with the system for the bare substrate.

APPLICATION

After the surface has been properly prepared and cleaned as above, apply two coats of this product (3 on bare wood) by brush or roller (Residential users). Commercial (non-residential) users may apply this product by airless spray while wearing the proper personal protective equipment.

NOTE: Important: Do not apply this product above the true waterline.