

REGISTERED
TRADE MARK
SIRROTTA'S
SIRCOFUME

97

SIROTTA'S

SIRCOFUME

5 G

LIQUID FUMIGATING

100% Non-Flammable!
100% Non-Explosive!

For Use In Vaults, Demolishing Chambers and Air

EASY-TO-FOLLOW INSTRUCTIONS

- 1. FOR FUMIGATION IN VAULTS OR AIR-TIGHT ROOMS DURING STORAGE: —**
 - (a) Use 1 gallon SIRCOFUME for each 1,000 cubic feet of vault space.
 - (b) SIRCOFUME can be fed into vault automatically or placed in fumigator. Or place SIRCOFUME in ducts or shallow pans. Pans or ducts should be placed above the level of the garments, near the ceiling, and evenly distributed throughout the vault. If possible, keep ventilating fans (but not exhaust fans) running during fumigation period. Where it is more convenient, the shallow pans or ducts may be placed on floor aisles and a fan placed so as to circulate the vapors throughout the vault.
 - (c) Maintain vault temperature at 70 degrees F. or higher during fumigation period of 8 hours or longer.
 - (d) Fumigate as often as necessary. Once a month is usually sufficient. A convenient time is on a week-end.

- 2.** If you have a demolishing or fumigation chamber garments before placing them in vault. Use from 2 to 3 gallons upon capacity and follow instructions 1 (b) and (c).

- 3. VAULTS, CHAMBERS OR ROOMS SHOULD BE THOROUGHLY VENTILATED BEFORE ENTERING.** To do this, use exhaust fan or open vault and ventilate into vault. For emergency entry, wear a gas mask appropriate for protection against organic fumigant vapors.

Buyer assumes all risks of use, storage or handling of material not in strict accordance with directions given.



Sirotta's Sircofume Liquid Fumigating Gas Is Classified By Underwriters' Laboratories, Inc. As Non-Flammable

CAUTION: KEEP OUT OF REACH OF CHILDREN. HARMFUL VAPOR. HARMFUL IF SWALLOWED. VOLATILE LIQUID. Avoid contact

with flame or hot surface. Contains chlorinated hydrocarbons. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Do not take internally. KEEP CONTAINER CLOSED TO PREVENT RUST AND EVAPORATION

USDA Registration No. 2826 1

PRODUCT OF U S A

BERNARD SIROTTA CO

33-35th STREET, BROOKLYN 32, N.Y.

World's Largest Manufacturer of All Chemicals & Equipment for

SIRCOFUME

5 GALLONS

D FUMIGATING GAS

For Use In Vaults, Demothing Chambers and Air-Tight Rooms

EASY-TO-FOLLOW INSTRUCTIONS

AIR-TIGHT ROOMS DURING STORAGE: —
 1000 cubic feet of vault space.
 automatically or placed in fumigator. Or place
 or ducts should be placed above the level
 evenly distributed throughout the vault. If
 exhaust fans) running during fumigation
 shallow pans or ducts may be placed on
 circulate the vapors throughout the vault.
 65 F. or higher during fumigation period
 e a month is usually sufficient. A con-

2. If you have a demothing or fumigation chamber or air-tight room, fumigate garments before placing them in vault. Use from 2 to 3 quarts SIRCOFUME depending upon capacity and follow instructions 1 (b) and (c)

3. VAULTS, CHAMBERS OR ROOMS SHOULD BE THOROUGHLY AERATED BEFORE ENTERING. To do this, use exhaust fan or open vault and allow fresh air to circulate into vault. For emergency entry, wear a gas mask approved by the U. S. Bureau of Mines for protection against organic fumigant vapors

Buyer assumes all risks of use, storage or handling of this material not in strict accordance with directions given herewith

PRODUCT OF U S A.

NO 20 9-67

Fumigating Gas Is Classified
 es, Inc. As Non-Flammable
 CHILDREN. HARMFUL VAPOR.
 D. VOLATILE LIQUID. Avoid contact
 rocarbons. Use with adequate ven-
 skin. Do not take internally. KEEP
 ORATION.

BERNARD SIROTTA CO. Established 1893

33-35th STREET, BROOKLYN 32, NEW YORK

World's Largest Manufacturer of All Chemicals & Equipment for Fur Cleaning and Storage