

Vinyzene® BP-5SIL3

1051
Pm 21
2004-105

FUNGISTATIC AND BACTERIOSTATIC AGENT FOR

PRECAUTIONARY STATEMENTS SILICONE CAULKING FORMULATIONS

HAZARDS TO HUMANS

DANGER

Corrosive, causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed.

FIRST AID

If splashed on skin, wash thoroughly with soap and water. If splashed in eyes, wash eyes immediately with copious amounts of water and secure medical attention immediately. Wash after handling.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DIRECTIONS FOR USE

NOTICE TO USER:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Triple rinse empty containers and other for recycling. Metal drums that cannot be reconditioned and recycled, should be punctured or crushed and disposed of in a landfill, or other procedures approved by state and local authorities.

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

VINYZENE BP-5SIL3 has as its carrier low viscosity dimethylsiloxane and is, therefore, compatible with most silicone formulations. Since VINYZENE BP-5SIL3 is a solution, it may be added, as all of the ingredients, during any stage of the mixing process. Temperatures up to 400° F. will not affect the product. Long term mixing or high shear conditions will have no effect.

VINYZENE BP-5SIL3 should be used at levels of 1.0 to 1.67% based on the weight of the finished formulation. For systems such as bathtub cavities or those used on the outside of a building, where excessive leaching occurs, the higher level should be employed.

Active ingredient:

10, 10'-oxybisphenoxarsine 2.0%
(Total arsenic as elemental As - 0.60%)
(Water soluble arsenic as elemental As - Less than 0.02%)

Inert ingredient:

98.0%

FOR ADDITIONAL INFORMATION REFER TO TECHNICAL DATA SHEET

Contains the toxic inert:NONYL PHENOL

READ THIS LABEL BEFORE USING
FOR INDUSTRIAL USE ONLY

DANGER

KEEP OUT OF REACH OF CHILDREN

Licensed for use under U.S. Patent No. 3,069,252

EPA REGISTRATION NO. 2829-105

EPA EST. REGISTRATION NO. 2529-IL-1

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

BEST AVAILABLE COPY

MORTON THIOKOL, INC.

Morton Products

NOV 2 1987

On the Federal Insecticide, Fungicide, and Rodenticide Act, for the pesticide registered under EPA Reg. No. 2829-105.