

VINYZENE® BP-5 SIL3

L3070-A

FUNGISTATIC & BACTERIOSTATIC AGENT FOR SILICONE CAULKING FORMULATIONS

Prod. No. 42216Z

ACTIVE INGREDIENTS:	
10,10'-OXYBISPHENOXARSINE	3.0%
(TOTAL ARSENIC AS ELEMENTAL As-0.60%)	
(WATER SOLUBLE ARSENIC AS ELEMENTAL As-LESS THAN 0.01%)	
INERT INGREDIENTS	97.0%
TOTAL	100.0%

CONTAINS THE TOXIC INGREDIENT NONYL PHENOL.

KEEP OUT OF REACH OF CHILDREN

WARNING

READ THIS LABELING BEFORE USING

FOR ADDITIONAL INFORMATION SEE MATERIAL SAFETY DATA SHEET

EPA REG. NO. 2829-105

U.S. EPA REG. NO. 2829-IL-1


PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not breathe spray mist. Avoid contact with eyes, skin or clothing. Wear a dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C or R95). Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

SEE RIGHT PANEL FOR ADDITIONAL PRECAUTIONS.



Morton Plastics Additives
150 Andover Street, Danvers, MA 01923-1480 508/774/3100
For medical emergency call CHEMTREC 1-800/424-9300



STATEMENT OF PRACTICAL TREATMENT IF EYE CONTACT: Flush immediately with water for at least 15 minutes. Call a physician. **IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. **IF ON SKIN:** Wash with plenty of soap and water. Get medical attention. **IF SWALLOWED:** Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. If person is unconscious, do not give anything by mouth and do not induce vomiting.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish, aquatic invertebrates, birds and mammals. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Triple rinse empty containers and offer for recycling. **Container Disposal:** Metal drums that cannot be reconditioned and recycled, should be punctured or crushed and disposed of in a landfill, or other procedures approved by state and local authorities. This container is hazardous when empty. Do not use heat, sparks, open flames, torches, cigarettes or near empty container since empty containers retain product residues (vapor, liquid or solids). All labeled hazardous precautions must be observed. Do not reuse empty container for food, clothing or products for human or animal consumption or skin contact without professional cleaning.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticides, spray mixture, or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your state pesticide or environmental control agency, or the hazardous waste representative at the nearest EPA Regional Office for guidance.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product should not be used on items which come into contact with food stuffs nor items of clothing or infant wear. Vinyzene BP-5SIL3 has as its carrier low viscosity dimethylsiloxane and is, therefore compatible with most silicone formulations. Since Vinyzene BP-5SIL3 is a solution it may be added, as all of the ingredients, during any stage of the mixing process. Temperatures up to 400°F will not affect the product. Long term mixing or high shear conditions will have no effect. Vinyzene BP-5SIL3 should be used at levels of 1.0 to 1.67% based on the weight of the finished formulation (that is, in-service compound composition). Vinyzene is recommended for use in shower curtains, floor coverings, wall coverings, coated fabrics, marine upholstery, automotive vinyl trim, vinyl molding, tarpaulins, awnings, gaskets, weather stripping, caulking, ditch liners, swimming pool liners, adhesives, coatings and specialty products, paper products, paper and plastic products, textiles, fibers and cordage, carpets, and other pesticides. Vinyzene BP-5SIL3 is particularly used for caulks, sealants, coatings and architectural use (building construction, maintenance and rehabilitation).

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risks of use and/or handling of this material when such use and/or handling is contrary to label instructions.

DRUM NO. 000 LOT NO.

NET WT.

PH 32
2829-105
11-10-97
1041