

ACCEPTED
 23 JUL 1974
 UNDER FEDERAL REGISTRATION ACT
 FUNGICIDE, RODENTICIDE AND
 FOR ECONOMIC POISON REGISTERED
 UNDER NO. 2841-10
 TO APPLICABLE COMMERCIAL

SAMPLE LABEL

NET
 CONTENTS

GALLONS

PHOENIX CREOSOTE

WOOD PRESERVATIVE

For open tank, brush or spray application. To control decay, rot, and termites. Fence posts, poles, foundation timbers, and heavy wooden members should be free of bark, dry and well seasoned and immersed in diluted product for a period of 12 to 48 hours to be effectively preserved. Other types of wood should have at least two flowing coats applied by the brush or spray method, or allow at least 3 minutes immersion by the open tank method of application. Dilute by adding one gallon of No. 2 fuel oil per gallon of creosote. Mix thoroughly.

ASSAY

ACTIVE INGREDIENTS: Coal Tar Creosote 98½%
 INERT INGREDIENTS 1½%



E.P.A. Reg. No. 2841-10

CAUTION

KEEP OUT OF REACH OF CHILDREN

May cause skin irritation. Use only with adequate ventilation. Avoid contact with skin. Avoid breathing of vapor. Harmful If Swallowed.

This product is toxic to fish and wildlife. Keep out of lakes, streams, and ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHOENIX OIL COMPANY

CHEMICAL DEPT. AUGUSTA, GEORGIA 30903

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.