

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND  
DOMESTIC ANIMALS  
WARNING**

Harmful or fatal if swallowed or absorbed through the skin. Do not get in eyes, on skin or on clothing. Avoid breathing spray mists or vapors. Wear goggles or face shield and rubber gloves when handling Copper Naphthenate.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

**PHYSICAL OR CHEMICAL HAZARDS**

Do not store or use near heat or open flame.

**STORAGE AND DISPOSAL**

**PESTICIDE DISPOSAL:** Pesticide, spray mixture or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, State or local procedures.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved State and local procedures.

**GENERAL:** Consult Federal, State or local disposal authorities for approved alternative procedures.

**WARRANTY STATEMENT**

Neither Shepard Chemical Works, Inc. nor the seller makes any representation or warranty, expressed or implied, concerning the use of this material, other than indicated on the label. Neither shall be held responsible in any manner for any personal injury or property damage or other type of loss resulting from improper handling, storage or use of this material. The buyer accepts and uses this material on these conditions.

**SHERARD'S  
COPPER NAPHTHENATE WOOD PRESERVATIVE**

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Apply liberally to all wood surfaces exposed to moisture or weather. Make certain all areas are fully treated to get maximum benefits.

Dip treatment is the most effective. A three minute immersion is adequate for most applications. Since a longer dip time achieves a higher retention of preservative in the wood, twelve to 48 hours immersion time is required for wood placed in contact with soil or large wooden structures. Wood should be free of bark, dry and well seasoned before treatment.

Brush or spray treatments are satisfactory for above ground applications, but should be used for ground contact applications only when dipping is not possible. In such cases, apply at least 2 liberal brush or spray treatments, allowing at least 1 hour between each coat.

This product is phytotoxic to plants. Avoid direct contact with plants during application.

Wood treated with COPPER NAPHTHENATE has a green color that fades slowly over time. Allow 24 hours or longer after application of the preservative prior to painting.

**RECOMMENDED USES**

COPPER NAPHTHENATE is recommended for all wooden items in contact with either fresh or salt water including boats, piers, and docks.

COPPER NAPHTHENATE may also be used on windows, window frames, stairs, porches, trellises, steps, fence pickets, fence rails, furring strips and arbors.

Powder Post beetles and termites are killed by application of this preservative. These insects will not attack properly treated wood. Copper Naphthenate also helps to control wood rot and decay.

**Keep Out of Reach of Children**

**WARNING**

**FIRST AID**

**IF IN EYES**—Immediately flush with large quantity of water and get medical attention.

**IF ON SKIN**—Flush with water. Remove and wash contaminated clothing before re-use.

**IF SWALLOWED**—Do not induce vomiting. CALL A DOCTOR.

See side panel for additional precautionary statements.

**1 GAL. NET**

**ACTIVE INGREDIENTS 100%**

*COPPER NAPHTHENATE .....	10%
PETROLEUM DISTILLATE .....	90%
TOTAL .....	100%
*EQUIVALENT TO METALLIC COPPER .....	1%

EPA REG. NO. 2900-3

EPA-EST. 2900-NC-1

This product contains 305 lbs. per gallon of Copper Naphthenate.

**SOLD BY**

**SHEPARD CHEMICAL WORKS, INC.**

Phone 791-0272 • P. O. Box 473 • WILMINGTON, N. C.

U. S. 74 East to Wrightsville Beach

**ACCEPTED**

26  
AUG 23 1985

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, this product is registered under EPA Reg. No. 2900-3