


Front Panel

SHEPARD'S  
ZINC NAPHTHENATE WOOD PRESERVATIVE - SOLVENT BASED  
CLEAR

Preserves Wood from Fungal Rot or Decay  
Protects Against Mildew and Prevents Fungal Stain  
Protects Wood Against Termite



Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Application

Can be used to preserve both interior which is subject to frequent or prolonged wetting (e.g. condensation or rain seepage) and exterior wood. Can be used for above ground, ground contact, and below ground uses. Below ground use requires a 5 minute to one hour dip depending on the degree of protection required. Wood to be treated should be dry and well-seasoned. Fence posts must have the bark removed. For fence posts, timbers or finished lumber to be buried in the soil, immersion for 12-48 hours provides long-term protection (pine species may be adequately penetrated in 6-8 hours). Cut timbers should be immersed 15 to 30 minutes per inch of thickness, except in case of the pine species which absorb the preservative at a faster rate. For termite and fungal rot protection, all wood should be treated after all cuts are made and before use.

Prevents warping, shrinking, swelling, checking, cracking, and water marking of the wood. Can be painted after drying for 24 hours. This product does not contain creosote or tar products and therefore can be painted with oil-base paint. For wood containing resins and other materials, weathering will enhance paint adhesion. This product offers a penetrant which is protective against sun, heat, cold, rain, salt spray and ultra-violet light.

Shepard's Zinc Naphthenate Wood Preservative should be applied liberally by brush, roller, spray or by dipping in a suitable container. The more wood preservative absorbed, the more effective the protection. Do not thin--material is supplied at proper application consistency.

Wood immersion should be for a minimum of three minutes if dipped.

A single coat is recommended for surfaces to be painted or stained.

On porous or rough wood that will remain clear, a second coat is recommended within the hour. Excess material not absorbed should be wiped off with a damp rag within minutes.

Front Panel (cont)

Clean equipment with mineral spirits or paint thinner immediately after completion of job for fast cleanup.

Fabric Protection

Can be used to protect and preserve fabric including rope, fish net, twine, canvas such as tentage and tarpaulins and burlap such as that used in nurseries and for ground cover. Such fabrics should be thoroughly saturated until wet and air dried before use. Material can be either sprayed or dipped for complete saturation and allowed to air dry for 24 hours before use. Fabric which will have extended skin contact or contact with food or feed should not be treated.

Wood Preservative Uses

Protects the following types of wood: shingles, millwork, windows, docks, piers, posts, pilings, block flooring, staking material, decks, spars, house siding, nursery lumber and slats.

Coverage

Square foot coverage depends on the porosity of wood and method of application but will be from 250 to 400 sq. ft. per gallon at 60° to 90° F.

Keep Out of Reach of Children (12 pt)

WARNING (18 pt)

See Other Precautionary Statements on Side Panel

Active Ingredients:

Zinc Naphthenate . . . . . 15.7%  
as Zinc metal - 2%

Inert Ingredients: . . . . . 84.3%

*6.83 lbs./gal.*

Total 100.0%

EPA Reg. No. 2900-

EPA Est. No. 2900-NC-1

Shepard Chemical Works, Inc.  
Phone: 919-791-0272 PO Box 473 Wilmington, NC  
U.S. 74 East to Wrightsville Beach

Side Panel

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND  
DOMESTIC ANIMALS  
WARNING

(18 pt)

Harmful if swallowed or absorbed through the skin. Do not get in eyes, on skin or on clothing. Avoid breathing spray mists or vapors. If swallowed, do not induce vomiting. Call a physician immediately. If absorbed through the skin, wash thoroughly with soap and water. If in eyes, flush with plenty of water and get immediate medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Contains petroleum distillate. Wear rubber gloves and protective clothing when handling freshly treated lumber. Do not store or use near heat or open flame.

STORAGE AND DISPOSAL

(12pt)

Pesticide Disposal: Pesticide, spray mixture or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, State or local procedures.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved State and local procedures.

General: Consult Federal, State or local disposal authorities for approved alternative procedures.

WARRANTY STATEMENT

Neither Shepard Chemical Works, Inc. nor the seller makes any representation or warranty, expressed or implied, concerning the use of this material, other than indicated on the label. Neither shall be held responsible in any manner for any personal injury or property damage or other type of loss resulting from improper handling, storage or use of this material. The buyer accepts and uses this material on these conditions.