

CONTENTS... 5 GALLONS

NOTICE

THOROUGHLY CLEAN EMPTY CONTAINER WITH APPLICATOR BRUSH OR RAGS. DESTROY EMPTY CONTAINER TO PREVENT REUSE. BURN OR BURY WASTE PESTICIDE & CLEANING RAGS. STAY OUT OF SMOKE. CLEAN UP SPILLS WITH PAINT THINNER OR OTHER PETROLEUM SOLVENT.

OSMOSE[®]

TRADE MARK

WOOD PRESERVING COMPOUND

From the
OSMOSE WOOD PRESERVING CO.

OSMOPLASTIC[®]

WARNING: May be fatal if swallowed. Can be absorbed through the skin. Do not breathe vapor. Do not get on skin, in eyes or on clothing. Causes skin irritation. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM DOMESTIC ANIMALS.

All waste pesticide should be removed from this container and empty container destroyed and buried.

ACTIVE INGREDIENTS:

Sodium Fluoride	43.70 %
Creosote	40.00 %
Potassium Bichromate	3.10 %
2,4-Dinitrophenol	2.00 %
Pentachlorophenol	1.98 %
Other Chlorophenols & Related Compounds	.22 %
	91.00 %

INERT INGREDIENTS

9.00 %
100.00 %

Directions for Use: Stir to an even consistency. Apply evenly with an ordinary paint or window brush. Area to be treated must be free from bark and all evidence of decay. Where treated area comes in contact with the ground, wrap with our water-proof bandage, OsmoShield.

USDA Reg. No. 3008-4

NOTE: Osmoplastic contains recognized salt preservatives used successfully in the art of wood preservation for more than 25 years. These salts (colorless) penetrate deeply into the wood and give lasting protection against decay.

ACCEPTED

APR 1971

3008-4

1/8 pt. OF REACH OF CHILDREN.

12 pt. type