

OSMOSE[®] K-33
WOOD PRESERVATIVE
(For Pressure Plant Use Only)

ACTIVE INGREDIENTS

Arsenic Pentoxide	34.0	%
Copper Oxide	14.5	%
Chromic Acid	26.5	%

INERT INGREDIENTS

Water	25.0	%
Total Arsenic as Metallic	22.2	%
Water Soluble Arsenic as Metallic	22.2	%

NET CONTENTS: 100 Kilograms (220.5 lbs)
157 lbs., Oxide Basis, Min.

91-2223
01-4-70

WARNING POISONOUS IF SWALLOWED

May cause rash or external ulcers. Wear goggles or face shield and rubber gloves when handling. Avoid contact with skin, eyes or clothing. In case of contact flush skin or eyes with plenty of water. For eyes get medical attention. Wash thoroughly after using. Wash clothing before re-use. Do not breathe spray mist.

All waste pesticide should be removed from this container and empty container decontaminated thoroughly before disposal in any other manner.

ANTIDOTE

Give two tablespoons of milk of magnesia or aluminium hydroxide gel suspended in water (the whites of two or three eggs may be used). Follow with an emetic (a tablespoon of mustard or table salt in a glass of warm water). Then give olive oil or mucilaginous drink. Never give anything by mouth to an unconscious person. CALL A PHYSICIAN IMMEDIATELY.

DIRECTIONS FOR DECONTAMINATION

Empty contents into mixing tank and flush container clean with 500 gallons of water which shall be reused for diluting treating solution.

DANGER KEEP OUT OF REACH OF CHILDREN

Re 36 b 9.69
Manufactured in Sweden by
BOLIDEN AKTIEBOLAG
SKELLEFTEHAMN

Imported by
OSMOSE WOOD PRESERVING CO
OF AMERICA, INC.
980 Ellicott St, Buffalo NY 14209

U.S.D.A. Reg. No. 3008-16