

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

(For Pressure Plant Use Only)

OSMOSE K-33-C is designed for the pressure impregnation of wood to provide protection against decay, termites and marine borers (Limnoria and Teredo).

Processes used to apply inorganic arsenical formulations will leave no visible surface deposits on the wood, as defined by AWPAC Standard C-1 and AWPB Standards LP2 and LP22. Visible surface deposits means a surface residue or crystallization on the treated wood. Small isolated or infrequent spots of chemical on otherwise clean wood shall be allowed.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not dispose of equipment washwaters or other wastes.

PHYSICAL OR CHEMICAL HAZARDS

Avoid contact with aluminum or zinc galvanized metal.

Note to User: Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets, and boots) required during application and handling of inorganic arsenicals are vinyl, polyvinyl chloride (PVC), neoprene, NBR (Buna-N), rubber, and polyethylene.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

RESTRICTED USE PESTICIDE

For retail sale to and use only by Certified Applicators or persons under their direct supervision, and only for those uses covered by the Certified Applicator's Certification.

OSMOSE[®] K-33-C (72%) WOOD PRESERVATIVE

(For Pressure Plant Use Only)

(Not For Use Or Storage In Or Around The Home)

ACTIVE INGREDIENTS:

Arsenic Pentoxide	24.5%
Copper Oxide	13.3%
Chromic Acid	34.2%

INERT INGREDIENT:

Water	28.0%
-------------	-------

100.0%

Total Arsenic as Metallic

Water Soluble Arsenic as Metallic


15.9%

15.9%

KEEP OUT OF REACH OF CHILDREN



**DANGER
POISON**



STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Induce vomiting by touching the back of the throat with finger. Avoid aspiration of vomit.

Do not induce vomiting of an unconscious person. Call a physician immediately.

IF INHALED: Remove victim to fresh air. Apply respiration if indicated. Call a physician immediately.

IF ON SKIN: Remove contaminated clothing and wash affected area with soap and water.

IF IN EYES: Flush eyes with plenty of water. Call a physician immediately.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Est. 3008-TN-1

E.P.A. Reg. No. 3008-17

MANUFACTURED BY



Osmose Wood Preserving, Inc.
980 Ellicott Street
Buffalo, New York 14209

NET CONTENTS: 275 LBS.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS

& DOMESTIC ANIMALS

DANGER: POISONOUS IF SWALLOWED OR ABSORBED THROUGH THE SKIN

Causes eye and skin irritation. Do not breathe vapor. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling and before eating or smoking. Wear eye protection devices and protective clothing and rubber gloves in all situations where dermal contact is expected. In case of contact flush skin or eyes with plenty of water. For eyes get medical attention. Wash clothing before reuse. Do not breathe spray mist.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g., cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves, and boots, impervious to the wood treatment formulation. In addition, individuals who enter pressure treatment cylinders must wear properly fitting, well-maintained, high efficiency filter respirators. MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10µg/m³) average over an 8-hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving tanks out of cylinders, mixing chemicals, and handling freshly treated wood).

Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and work shoes, boots and equipment at the plant. Worn-out protective clothing and work shoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with state and federal regulations.

Individuals in the work area of an arsenical wood treatment plant must wear properly fitting, well-maintained high efficiency filter respirators. MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10µg/m³) average over an 8-hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

ACCEPTED

Sept 3, 1992

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under
EPA Reg. No. 3008-17

This product is toxic to fish and wildlife. Do not apply directly to water, areas where surface water is present or to intertidal areas below the mean high water mark. Do not apply where runoff is likely to occur. Do not contaminate water when disposing of equipment washwaters.