

## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### APPLICATION INSTRUCTIONS

#### A. DIRECT APPLICATION

1. Open can after reaching working position near pole top.
2. Pour contents uniformly over pole roof prior to installation of POLE TOPPER protective pad.

#### B. INDIRECT APPLICATION

1. Simple tipping devices can be worked out with standard hot stick equipment when it is desired to apply POLE TOPPER FLUID from position below hot wires.

#### C. SPECIAL SITUATIONS

1. **TEMPERATURE:** POLE TOPPER FLUID can be applied in temperatures suited to normal working conditions.
2. **WET SURFACES:** POLE TOPPER FLUID can be applied to damp surfaces but should not be applied over ice.
3. **CRITICAL DECAY:** The contents of one can is ample for thorough preservation of the normal pole roof. More than one can may be required if, in the judgment of the applicator, severe hollows indicate the need in order to achieve complete saturation.

### STORAGE AND DISPOSAL

**STORAGE:** Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent) and offer for recycling or reconditioning or dispose of in a sanitary landfill, or by other approved State and Local procedures.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment or disposal of wastes.

### PHYSICAL OR CHEMICAL HAZARD

Do not use, pour, spill or store near heat or open flame.

## RESTRICTED USE PESTICIDE

For retail sale to and use only by Certified Applicators or persons under their direct supervision, and only for those uses covered by the Certified Applicator's Certification.

# POLE TOPPER FLUID

10% penta wood preservative designed for application to roof area of poles of all species and types of original treatment prior to installation of POLE TOPPER protective pad.

#### ACTIVE INGREDIENTS:

Pentachlorophenol\* ..... 8.9%  
Other Chlorinated Phenols and Related Compounds ..... 1.1%

**INERT INGREDIENTS:** ..... 90.0%

\*Equivalent to 10% Technical Pentachlorophenol As Determined by Federal Specification TT-W-570.

### KEEP OUT OF REACH OF CHILDREN DANGER

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

#### STATEMENT OF PRACTICAL TREATMENT

**IF SWALLOWED:** Induce vomiting by touching the back of the throat with finger. This product contains petroleum distillates; avoid aspiration of vomit. Do not induce vomiting of an unconscious person. Call a physician immediately.

**IF INHALED:** Remove victim to fresh air. Apply respiration if indicated. Call a physician immediately.

**IF ON SKIN:** Remove contaminated clothing and wash affected area with soap and water.

**IF IN EYES:** Flush eyes with plenty of water. Call a physician immediately.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS  
EPA Est. 3008-NY-1      EPA Registration No. 3008-19

MANUFACTURED BY



Omosee Wood  
Preserving, Inc.  
900 Ellwood Street  
Buffalo, NY 14209

NET CONTENTS: 12 FLUID OZ.

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER:** May be fatal if swallowed, inhaled or absorbed through the skin. Causes eye and skin irritation. Do not breathe vapors or spray mist. Use only with adequate ventilation. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling and before eating or smoking. Wear protective clothing and rubber gloves when handling freshly treated lumber.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is MSHA/NIOSH-approved for organic vapors and acid gases.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear long-sleeved shirts, long pants and impervious gloves (e.g., vinyl coated). Wash exposed skin thoroughly after contact with treated wood, and before eating, drinking or using tobacco products.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (for example, during the actual application process and when handling freshly treated wood).

Applicators who apply pentachlorophenol by other application methods (e.g., brush-on) must wear long sleeved shirts, long pants, and an impermeable apron. Launder protective clothing separately from other household laundry. Applicators must not eat, drink or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Dispose of worn-out protective clothing and workshoes or boots in any general landfill in the trash, or in any other manner approved for pesticide disposal.

**Note to user:** As used on this label the term "respirators" means properly fitting, well-maintained half-mask canister or cartridge respirators which are MSHA/NIOSH-approved for organic vapors and acid gases. Examples of acceptable impervious materials for protective clothing (e.g., vinyl, jackets, head covering, boots, and gloves) required during application and handling of pentachlorophenol are polyvinyl acetate (PVA), polyvinyl chloride (PVC), neoprene, NBR (Buna-N), and nitrile.

