

5

1 TO 10 CONCENTRATE

FOR PREVENTION AND CONTROL OF FUNGAL DECAY IN WOOD

DIRECTIONS

To make a ready-to-use solution, containing 5% by weight of pentachlorophenol, mix one part of PCP 1-10 concentrate with ten parts by volume of a petroleum solvent weighing approximately 7.0 lbs. per gallon.

Properly diluted formulation is used for treatment of wood by flooding the surface, total immersion or pressure treatment for the prevention and control of fungal decay organisms.

Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver.

Lumber intended to be in contact with the soil should be dipped for a minimum 3 minutes or if treated by the brush or spray method, receive two or more flowing coats of the product.

WARNING

KEEP OUT OF REACH OF CHILDREN

May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Causes skin irritation. Do not breathe vapors or spray mist. Use only with adequate ventilation. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Wear protective clothing and rubber gloves when handling freshly treated lumber.

In case of contact wash thoroughly with soap and water. For eyes get medical attention.

NOTICE

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

All pesticide should be removed from this container and empty container destroyed and buried.

OSMOSE

Pentachlorophenol*	35.86%
Other chlorophenols and related compounds	4.17%
Aromatic petroleum solvent	41.30%

81.33%
18.67%
<u>100.00%</u>

CONTENTS

5 GALLONS

*Equivalent to 41.7% by weight of technical pentachlorophenol as defined in Fed. Spec. TT-W-570.

EPA Reg. No. 3008-25

OSMOSE WOOD PRESERVING CO. OF AMERICA, INC. • BUFFALO, N. Y. 14209

FOR PREVENTION AND CONTROL OF FUNGAL DECAY IN WOOD

FOR PREVENTION AND CONTROL OF FUNGAL DECAY IN WOOD

DIRECTIONS

To make a ready-to-use solution, containing 5% by weight of pentachlorophenol, mix one part of PCP 1-10 concentrate with ten parts by volume of a petroleum solvent weighing approximately 7.0 lbs. per gallon.

Properly diluted formulation is used for treatment of wood by flooding the surface, total immersion or pressure treatment for the prevention and control of fungal decay organisms.

Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver.

Lumber intended to be in contact with the soil should be dipped for a minimum 3 minutes or if treated by the brush or spray method, receive two or more flowing coats of the product.

WARNING

KEEP OUT OF REACH OF CHILDREN

May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Causes skin irritation. Do not breathe vapors or spray mist. Use only with adequate ventilation. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Wear protective clothing and rubber gloves when handling freshly treated lumber.

In case of contact wash thoroughly with soap and water. For eyes get medical attention.

NOTICE

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

All pesticide should be removed from this container and empty container destroyed and buried.

Pentachlorophenol*	35.86%
Other chlorophenols and related compounds	4.17%
Aromatic petroleum solvent	41.30%
	81.33%
	18.67%
	100.00%

*Equivalent to 41.7% by weight of technical pentachlorophenol as defined in Fed. Spec. TT-W-570.

EPA Reg. No. 3008-25

OSMOSE WOOD PRESERVING CO. OF AMERICA, INC. • BUFFALO, N. Y. 14209