OSMOSE K-33 (40%)

WOOD PRESERVATIVE

(For Pressure Plant Use Only)

DIRECTIONS FOR USE: TO BE USED IN ACCORDANCE WITH AWPA OR FEDERAL SPECIFICA-TIONS. REFER TO OSMOSE OPERATING MANUAL FOR SPECIFIC RECOMMENDATIONS.

ACTIVE INGREDIENTS

Arsanic Pentoxide 18.0% Chromic Acid` 14.1% Copper Oxide 7.9%

TOTAL ARSENIC AS METALLIC WATER SOLUBLE

INERT INGREDIENTS

60.0% 100.0%

UNDER THE FEOCHT ME

FUNGICIDE AND DOD! FOR ECONOMICE DICENT

NET CONTENTS: 600 Pounds

240 lbs. Oxide Basis, Min. UNITE NO. 3008-35





DANGER-POISON

POISONOUS IF SWALLOWED

M ause rash are action al ulcers. Wear goggles or face shield and rubber gloves when handi. a Avoid contact with skin, eyes or clothing. In case of contact flush skin or eyes with plenty of water. For eyes get medical attention. Wash thoroughly after using. Wash clothing before re-use. Do not breathe spray mist.

All waste pesticide should be removed from this container and empty container decontaminated thoroughly before disposal in any other manner.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes.

FIRST AID

Give two tablespoons of milk of magnesia or aluminum hydroxide gel suspended in water (the whites of two or three eggs may be used). Follow with an emetic (a tablespoon of mustard or table salt in a glass of warm water). Then give olive oil or mucilaginous drink. Never give anything by mouth to an unconscious person. CALL A PHYSICIAN IMMEDIATELY.

DIRECTIONS FOR DECONTAMINATION.

Empty contents into mixing tank and flush container clean with 500 gallons er which shall be reused for diluting treating solution. Puncture and safely bury cleaned container.

DANGER KEEP OUT OF REACH OF CHILDREN

Manufactured by

OSMOSE WOOD PRESERVING CO. OF AMERICA, INC. 960 Ellicott St. Buffalo NY 14209

E. P. A. Reg. No. 3008-35

EPA Est. 3008-TN-1