

TREATMENT FOR ALL STANDING POLES

# OSMOPENTA

## WOOD PRESERVING COMPOUND

3008-37

Oct. 14, 1975

KILLS EXISTING FUNGUS ORGANISMS

INHIBITS NEW FUNGUS GROWTH

### DESCRIPTION

OSMOPENTA is a Wood Preserving Compound with penetration and retention characteristics for long-lasting treatment of standing poles in above and below ground applications. Special inert ingredients assure ease of application and contribute to maximum penetration and retention of preservative.

### DIRECTIONS

Remove existing decayed wood if present. Apply with long fiber window brush. Brush out to even  $\frac{1}{4}$ " thickness. For groundline treatment apply to area 15" below and 3" above ground line. Apply durable plastic coated paper wrapping over entire treated area before back filling. For application to dry wood above ground wrapping is not required. Make liberal application into splits, checks and bolt holes.

### WARNING

#### KEEP OUT OF REACH OF CHILDREN

Harmful or fatal if swallowed or absorbed through skin. Do not breathe vapor. Do not get on skin, in eyes, or on clothing. Causes skin irritation. Wash thoroughly after handling.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on the label.

All waste pesticide should be removed from this container and empty container destroyed and buried.

#### KEEP AWAY FROM DOMESTIC ANIMALS

Thoroughly clean empty container with applicator brush or rags. Destroy empty container to prevent reuse. Burn or bury waste pesticide and cleaning rags. Stay out of smoke. Clean up spills with paint thinner or other petroleum solvent.

#### ACTIVE INGREDIENTS:

|                                          |        |
|------------------------------------------|--------|
| Pentachlorophenol*                       | 8.96%  |
| Other chlorophenols and related compound | 1.04%  |
| Petroleum Distillate                     | 57.20% |

#### INERT INGREDIENTS:

|       |         |
|-------|---------|
|       | 32.80%  |
| Total | 100.00% |

OSMOSE

CONTENTS

42

Pounds  
Net

\*Equivalent to 10.4% technical pentachlorophenol as determined by Federal Specifications TT-W-570.

OSMOSE WOOD PRESERVING CO. OF AMERICA, INC. • BUFFALO, N. Y. 14209

E.P.A. Reg. No. 3008-37

EPA Est. 3008-NY-1