

Teri Muchow  
Osmose Wood Preserving, Inc.  
980 Ellicott St.  
Buffalo, NY 14209

Dear Ms. Muchow:

Subject: Revised Directions for Use  
COP-R-PLASTIC Wood Preserving Compound  
EPA Registration No. 3008-55  
Your Submission Dated October 12, 1994

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended is acceptable provided that you:

1. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:

a. Modify the application rate, since the proposed directions are unclear. We assume you mean to apply to a thickness of 1/16" on poles or timber.

b. Modify the directions for use to read similar to the following:

Fill drilled holes, decay pockets, and voids using a grease gun or other pressurized applicator.

2. Submit one (1) copy of your final printed labeling before you release the product for shipment.

A stamped copy of the labeling is enclosed for your records.

Sincerely yours,



Cynthia Giles-Parker  
Product Manager (22)  
Fungicide Herbicide Branch  
Registration Division (7505C)

Enclosure

243

## DESCRIPTION

COP-R-PLASTIC is designed for remedial treatment of in-service poles, piling, posts and other timber members. It may be applied by brush, trowel or pump.

## DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**EXTERNAL TREATMENT:** Apply at a rate of 1/16" to pole or timber exterior. Typical pole application is from 3" above to 18" below groundline and lower where deeper decay is suspected. Application on poles to be restored should extend the length of wrap-around type repair systems. Wrap treated area with water-proof bandage, OSMOSHIELD.

**INTERNAL TREATMENT:** For control of internal decay in poles and other timbers, holes may be drilled in areas of the pole or timber where protection is required. Fill decay pockets and voids using a grease gun or other pressurized applicator. Plug application holes with secure-fitting dowels.

## STORAGE AND DISPOSAL

### STORAGE:

Do not contaminate water, food or feed by storage or disposal.

### CONTAINER DISPOSAL:

Triple rinse (or equivalent). Puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke

If product is in metal container, do not attempt to burn or incinerate. Triple rinse (or equivalent). Puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

### PESTICIDE DISPOSAL:

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

INDUSTRIAL USE ONLY. NOT FOR HOUSEHOLD USE

# COP-R-PLASTIC™ WOOD PRESERVING COMPOUND

## ACTIVE INGREDIENTS:

Sodium Fluoride .....	44.4% /
Copper Naphthenate* .....	20.0%
Inert Ingredients ** .....	35.6%
TOTAL .....	100.0%

\*Equivalent to 2.0% Copper as Metal

\*\*Contains Petroleum Distillates

## KEEP OUT OF REACH OF CHILDREN DANGER STATEMENT OF PRACTICAL TREATMENT

**If in eyes:** Hold eyelids open and flush with a steady gentle stream of water for 15 minutes. Get medical attention immediately.

**If swallowed:** Drink promptly large quantities of milk, egg white, gelatin solution, or, if these are not available, large quantities of water. Avoid alcohol. Do not induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get immediate medical attention.

**If on skin:** Wash with plenty of soap and water. Get medical attention.

Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

NET CONTENTS 5 GALLONS (18.93 L.)

DE  
COP-R-PLASTIC  
preservatives used  
wood preservation  
This combination  
naphthenate pro  
tion against decay  
COP-R-PLASTIC  
ground-line treat  
and other timbers

PRE  
S  
HAZARDOUS  
DOM

DANGER: Corro  
damage may be  
absorbed through  
skin or on clothing  
goggles. Wash t  
after handling an  
using tobacco.

ENV

This pesticide is  
apply directly to  
water is present  
mean high water  
water when disp  
washwaters.

P  
CHEM

Do not use, poi  
flame.

WOC

Bu  
E  
E.P.A.



BEST AVAILABLE

308

NOV 10 1955

NOV 10 1955

ACCEPTED  
with COMMENTS  
In EPA Letter Dated:

NOV 10 1955

Under the Federal Insecticide  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

3008-55