

**RESTRICTED USE PESTICIDE
DUE TO CARCINOGENICITY**

FOR RETAIL SALE TO AND USE ONLY BY CERTIFIED APPLICATIONS OR PERSONS UNDER THEIR DIRECT SUPERVISION, AND FOR THOSE USES COVERED BY THE CERTIFIED APPLICATOR'S CERTIFICATION.

**ACC 50%
WOOD PRESERVATIVE**

(For Pressure Plant Use Only)
(Not For Use Or Storage In Or Around The Home)

ACTIVE INGREDIENTS:

Copper Oxide.....14.07%
Chromic Acid.....35.46%

INERT INGREDIENTS:.....50.47%

Total 100.00%

Metallic Copper Equivalent.....11.31%

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

If inhaled	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth to mouth, if possible. Call a poison control center or doctor for further treatment advice.
If on skin or clothing	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice
If in eyes	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
If swallowed	Call poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment.	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.	

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS


EPA EST. NO. 3008-TN-1

EPA REG. NO. 3008-60

Osmose®

Osmose, Inc.
980 Ellicott Street
Buffalo, NY 14209

NET CONTENTS:



283

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
(For Pressure Plant Use Only)

ACC 50% WOOD PRESERVATIVE is designed for the pressure impregnation of wood to provide protection against decay, termites and marine borers. (Limnoria and Teredo).

ACC 50% Wood Preservative is for the preservative treatment of wood by pressure process according to American Wood Preservers' Association (AWPA) Use Category System: Processing and Treatment Standard T1. ACC 50% Wood Preservative must be diluted, prior to use to meet AWPA Treatment Standard T1, to between 0.5% to 7% active ingredients in treating solution. Dilution rate will vary based on wood species, treatment cycle and final retention.

Processes used to apply ACC 50% WOOD PRESERVATIVE shall leave no visible surface deposits on the wood. (Visible surface deposits means a surface residue or crystallization on the treated wood. Small isolated or infrequent spots of chemical on otherwise clean wood shall be allowed.)

This product may only be used for preservative treatment of the following categories of forest products and in accordance with the respective cited standard (T1) of the 2001 edition of the American Wood Preservers' Association (AWPA) standards: Lumber and Timber for mine ties and bridge ties, Lumber and Timber for salt water use (also includes brackish water only (C2), Piles (C3); Poles (C4); Wood for Highway Construction (C14); Round, Half Round and Quarter Round Fence Posts (C16); Poles, Piles and Posts Used as Structural Members on Farms (C16); Wood for Marine Construction for Salt Water Use (also includes brackish water) immersion and/or subject to saltwater (or brackish water) splash ["subject to saltwater (or brackish water) splash" means any member of a marine structure which is positioned above mean high tide but is subject to frequent wetting from wave action], [Pilings (round and square), and Timbers; Walers, Framing, Stringers and Cross Bracing (2" x 6" and/or 3"x6" and larger nominal dimensions and treated to a minimum of 0.60 pcf) (C18); Round Poles and Posts Used in Building Constructions (C23); Sawn Timber Used To Support Residential and Commercial Structures (C24); Sawn cross arms (C25), Structural Glued Laminated Members and Laminations Before Gluing (C28), Structural Composite Lumber (C33), and Shakes and Shingles (C34); and in accordance with the respective cited standard (T1) of the 2002 edition of the American Wood-Preservers' Association Standards; Lumber and Timbers for Cooling Towers (C30). Forest products treated with this product may only be sold or distributed for uses within the AWPA Commodity Standards under which the treatment occurred.

CONSUMER INFORMATION TAG (CIT)

Treater shall place a Consumer Information Tag (CIT) on each piece of wood treated with ACC 50% Wood Preservative. The CIT shall conform to the form below and shall be firmly attached to each piece of treated wood.

1. The consumer information tag shall have the following minimum dimensions: 0.625 by 2.5 inches.
2. The consumer information tag shall include the following statements on the tag:

OBTAIN CONSUMER INFORMATION SHEET AT: www.chromesafety.org

Copper and Chromium are in the pesticide applied to this wood. Chemicals may migrate from treated wood or be dislodged from the wood surface. Use respiratory protection, gloves, and goggles when sanding, cutting or handling. Cut outdoors. After working with this wood, wash exposed skin thoroughly and wash work clothes separately from other clothing. DO NOT USE this wood where it may come into contact with drinking water except for incidental contact such as fresh water docks. Do not use in direct contact with food, animal feed, or beehives. Do not use this wood, saw dust, chips or scraps for mulch or burn in open fires or in stoves, fireplaces or residential boilers. Product performance will vary by installation location.

ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer treatment plant authority. For guidance contact your State Water Board or Regional Office of the Environmental Protection Agency.

PHYSICAL OR CHEMICAL HAZARDS

Avoid contact with aluminum or zinc galvanized metal.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your state Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed or absorbed through skin. Harmful if inhaled. Do not get in eyes, on skin, or on clothing. Wear face shield, protective clothing and rubber gloves. Avoid breathing vapor or mist. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

PERSONAL PROTECTIVE EQUIPMENT:

Applicators and other handlers working with or around concentrate or wood treatment solutions must wear:

- coveralls, long-sleeved shirt and long pants,
- socks and chemical resistant foot wear,
- goggles or face shield, and
- chemical resistant gloves (such as barrier laminate or butyl nitrile/neoprene rubber, PVC, viton at ≥ 14 mils).

For mixing/loading: Wear chemical resistant apron.

USER SAFETY REQUIREMENTS:

Follow manufacturers' instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

Applicators and other handlers must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g. handling freshly treated wood).

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and work shoes or boots and equipment at the plant. Worn-out protective clothing and work shoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with state and federal regulations.

Individuals in the work area of a wood treatment plant using ACC 50% Wood Preservative must wear properly fitting, well-maintained, high efficiency filter respirators MSHA/NIOSH-approved for hexavalent chromium, if the level of hexavalent chromium in the work area exceeds or can reasonable be expected to exceed 1.0 micrograms per cubic meter of air ($1.0 \mu\text{g}/\text{m}^3$) average over an 8-hour work period or is unknown. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with 20 CFR Parts 1910, 1915, and 1926.

USER SAFETY RECOMMENDATIONS:

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g. manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

Users must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.