PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING:

May be fatal if swallowed. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Applicators must wear rubber gloves in all situations where dermal contact is expected.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark.

STORAGE AND DISPOSAL

STORAGE: Store in a cool place. Avoid excessive heat.

PESTICIDE DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Wastes resulting from the use of this product may be disposed of on site, or at an approved waste disposal facility.

CONTAINER DISPOSAL: Completely empty bag. Then dispose of by incineration, or if allowed by State and local authorities, by burning. If burned, stay out of smoke.



FLURODS™

This product is for commercial purposes only. Not for household use

ACTIVE INGREDIENTS:

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting on or give anything by mouth to an unconscious person.

IF INHALED: Remove victim to fresh air. Apply respiration if indicated. Call a physician immediately.

IF ON SKIN: Remove contaminated clothing and wash affected area with soap and water.

IF IN EYES: Flush eyes with plenty of water. Call a physician immediately.

SEE SIDE PANELS FOR PRECAUTIONARY STATEMENTS EPA Est. No. 3008-NY-1 EPA Reg. No. 3008-63

Manufactured By:
Osmose Wood Preserving, Inc.
980 Ellicott Street
Buffalo, New York 14209

NET CONTENTS: _____

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FLURODS are recommended for the remedial treatment of wood products (poles, posts, timbers, crossties, etc.) to arrest internal decay. FLURODS preservative cartridges are inserted into holes drilled into those parts of the wood structure susceptible to decay.

The dosage of FLURODS is dependent on the volume of wood to be treated. The recommended minimum dosage is 39.2 grams per cubic foot of wood to be protected.

Drill a hole or holes that will accommodate the number of FLURODS needed. After insertion of the FLURODS, cap with a wood or plastic plug, or seal with a filler such as putty. The moisture which is typically present in decay susceptible wood dissolves the sodium fluoride active ingredient in FLURODS which then diffuses into the wood.

PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame.

NOTE

Seller makes no warranty, expressed or implied concerning this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to labels instructions.

NOT REVIEWED
In Accordance with PR Notice 82-2
Based On Draft Labeling Dated

4-12-96

4/12/10

 \Im

 α

 σ