

DESCRIPTION

OSMOPLASTIC contains recognized salt preservatives used successfully in the art of wood preservation for more than forty (40) years. These colorless salts penetrate deeply into the wood and give long-lasting protection against decay.

OSMOPLASTIC is designed for remedial treatment of in-service poles, piling, posts and other timber members. It may be applied by brush, trowel or pump.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Stir to an even consistency.

EXTERNAL TREATMENT: Apply at a rate of 1/16" to pole or timber exterior. Typical pole application is from 3" above to 18" below groundline and lower where deeper decay is detected. Application on poles to be restored should extend the length of wrap-around type repair systems. Wrap treated area with waterproof bandage, OSMOSHIELD.

INTERNAL TREATMENT: For control of internal decay in poles and other timbers, holes may be drilled in areas of the pole or timber where protection is required. Fill decay pockets and voids using a grease gun or other pressurized applicator. Plug application holes with secure fitting dowels.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal.

DISPOSAL: Completely empty bag into application equipment. Then dispose of empty bag in a sanitary landfill or by incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Proper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instruction, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

PHYSICAL OR CHEMICAL HAZARDS

Do not use, pour, spill or store near heat or open flame.

APR 17 1998

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 3008-68

RESTRICTED USE PESTICIDE

DUE TO ONE INGREDIENT, CREOSOTE, WHICH IS LINKED TO CHRONIC TOXICITY IN ANIMAL STUDIES. For retail sale to and use only by Certified Applicators or persons under their direct supervision, and only for those uses covered by the Certified Applicators' certification.

GROUNDLINE TREATMENT FOR ALL STANDING POLES

OSMOPLASTIC-SD

WOOD PRESERVING COMPOUND

ACTIVE INGREDIENTS:

Sodium Fluoride 44.42%

Creosote 45.62%

Sodium Dichromate 3.20%

INERT INGREDIENTS: 6.76%

Total 100.0%

KEEP OUT OF REACH OF CHILDREN
DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Call a physician or poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching the back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

IF INHALED: Remove victim to fresh air. Apply respiration if indicated. Call a physician immediately.

IF ON SKIN: Remove contaminated clothing and wash affected area with soap and water. Get medical attention.

IF IN EYES: Flush eyes with plenty of water. Call a physician immediately.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS
EPA Registration No. 3008-68 EPA Est. 3008-NY-1



Osmose Wood Preserving, Inc.
980 Ellicott Street
Buffalo, NY 14209

NET CONTENTS: 5 Gallons (18.93 L.)

pm 34
3008-68
4/17/98
page 132

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: May be fatal if swallowed, inhaled or absorbed through the skin. Causes eye and skin irritation. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. May cause severe burns. Wash thoroughly after handling and before eating or smoking. Do not take internally. Use with adequate ventilation.

Applicators must wear gloves impervious to the wood treatment formulations (e.g. polyvinyl acetate [PVA], polyvinyl chloride [PVC], or neoprene) in all situations where dermal contact is expected (e.g., during the actual application process and when handling freshly treated wood).

Applicators must wear long sleeves, long pants, and an impermeable apron during the application and mixing processes and all situation where dermal contact is expected.

Work clothing must be changed when it shows signs of contamination. Launder work clothing separately from other household laundry. Dispose of worn-out work clothing and work shoes or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation. Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional office of the EPA.

Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not apply where runoff is likely to occur. Do not contaminate water when disposing of equipment washwaters.