



CHROMATED ZINC CHLORIDE SOLUTION

ACTIVE INGREDIENTS:

Zinc Chloride ----- 16.28%
Sodium Dichromate ----- 3.72%

INERT INGREDIENTS:

Water ----- 80.00%

This Chromated Zinc Chloride conforms to the specifications of the
American Wood Preservers Association

For use only for application to exposed surfaces when cutting or notching
Chromated Zinc Chloride pressure-treated lumber.

DIRECTIONS: STIR CONTENTS AND USE FULL STRENGTH. APPLY SEVERAL
COATS WITH BRUSH OR RAG MOP TO ALL SURFACES OF CHROMATED ZINC CHLORIDE
PRESSURE-TREATED LUMBER THAT HAS BEEN EXPOSED BY CUTTING, NOTCHING
OR DAPPING.

USE WITH CAUTION STRICTLY IN ACCORDANCE WITH DIRECTIONS

Sold only for protection of lumber against termites and decay-producing fungi.

CAUTION: KEEP OUT OF REACH OF CHILDREN
HARMFUL IF SWALLOWED. AVOID CONTACT WITH SKIN, EYES OR CLOTHING.
WASH AFTER HANDLING.

Destroy all empty containers.

J. H. BAXTER
1700 SOUTH EL CAMINO REAL
SAN MATEO, CALIFORNIA 94402
E.P.A. Reg. No. 3098-12

NET CONTENTS _____ GALS

ACCEPTED WITH COMMENTS