

ONE QU

SEAL-TOX PREPARED is ready for use, non-swelling, paintable, transparent, toxic water-repellent preservative containing the recommended 5% of chlorinated phenols for protection of wood against wood-destroying organisms and insects. It penetrates into cracks, ends, joints, etc., giving added protection to portions often poorly protected by surface coatings.

APPLICATION DIRECTIONS

Thoroughly clean the surface, removing all dirt, dust, and bark. Apply only to dry, well-seasoned wood and at a temperature of 60° F. or higher. Apply by dipping if possible; a 3-minute dip is standard for ordinary service. For more severe conditions, wood may be dipped longer or for several hours. Where dipping is not practical, good results may be had by applying several brush coats, as much as will be absorbed. Apply liberally to ends, cracks, and joints.

COVERAGE: About 300 sq. ft. per gallon, depending on kind and condition of wood.

CAUTION



POISON

Do not expose any part of the body to the solution. Wear protective garments. Rubber gloves should be worn when handling wood being treated.

Do not permit liquid to be handled by employees who have skin eruptions, acne or pimples, or who have, thru accident, skin abrasions or burns or chapped hands. If this preparation comes in contact with the skin, wash off with soap and warm water, kerosene, or mineral spirits. In case of accidental swallowing of the solution, an emetic, such as mustard and water, should be given to produce vomiting. Call a physician.

USES

SEAL-TOX is used where a toxic preservative, which may be painted over, is needed. It will protect woods against rot stain, mold, decay, termites, and nearly all forms of boring insects. It is excellent for exterior millwork, sash, doors, trim, siding, sills, joists, porch floors, steps, etc.



USDA REG. NO. 31

SEAL-TOX PREPARED

A water-repellent transparent wood preservative. Used as a primary and boring insect control are desirable. Repellence is necessary.

Active ingredients

Mineral Spirits
Dicyclopentadiene Linseed Oil Copolymer
Phenolic-tung Oil Varnish
Pine Oil
*Pentachlorophenol
Cobalt, Lead, Calcium Naphthenate driers

*Meets Federal Specification TT-W-5
412-467

ONE QUAL

WARNING

**THIS PRODUCT IS POISONOUS TO FISH
KEEP OUT OF LAKES, STREAMS, AND PONDS**

**ARM-
BRAND**



WOOD FINISHES • PRES

U.S. PAT. REG. NO. 37
SEAL-TOP
PREPARED



WARNING! (READ CAREFULLY)

**THIS PRODUCT CONTAINS
PETROLEUM DISTILLATE. If Swal-
lowed, Do Not Induce Vomiting.
CALL PHYSICIAN IMMEDIATELY.
COMBUSTIBLE. Keep away from
heat and open flame. Use with
adequate ventilation. Avoid pro-
longed contact with skin and
breathing of vapor or spray mist.
Do not transfer contents to
bottles or other unlabeled con-
tainers. Close container after
each use.**

**KEEP OUT OF REACH
OF CHILDREN**

**MANUFACTURED BY
FORMAN-FORD PAINTS, INC.
MINNEAPOLIS MINNESOTA 55427**

A DIVISION OF BALTIMORE
PAINT & CHEMICAL CORPORATION

CAUTION

**HARMFUL OR FATAL IF S
KEEP OUT OF REACH O
SEE LEFT SIDE AND BACK
ADDITIONAL CAU**