



OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

WASHINGTON, D.C. 20460

February 12, 2026

SENT BY EMAIL

David Swain
david.swain@srcconsultants.com
ALBEMARLE CORPORATION

Subject: Labeling Notification per Pesticide Registration Notice (PRN) 98-10 - Add Optional Size to Label
Product Name: ALBEMARLE S909 BIOCIDE
Admin Number: 3377-55
EPA Receipt Date: 12/19/2025
Action Case Number: 00680713

Dear David Swain:

The U.S. Environmental Protection Agency is in receipt of your application for notification under Pesticide Registration Notice 98-10 for the above referenced product. The EPA has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The labeling submitted with this application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to your company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide, Fungicide, and Rodenticide Act and is subject to review by the EPA. If the website is false or misleading, the product will be considered to be misbranded and sale or distribution of the product is unlawful under FIFRA section 12(a)(1)(E). 40 CFR § 156.10(a)(5) lists examples of statements the EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the EPA find or if it is brought to our attention that a website contains statements or claims substantially differing from statements or claims made in connection with obtaining a FIFRA section 3 registration, the website will be referred to the EPA's Office of Enforcement and Compliance Assurance.

If you have questions, please contact LaShonda Bunch via email at bunch.lashonda@epa.gov.

Sincerely,

A handwritten signature in black ink that reads "Demson Fuller".

Demson Fuller, PM Team Lead
RMB1, AD
Office of Pesticide Programs

NOTIFICATION

3377-55

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

02/12/2026

ALBEMARLE S909 BIOCIDE

FOR USE AS A FUNGICIDE, ALGICIDE, SLIMICIDE AND MICROBIOCIDE IN
RECIRCULATING COOLING AND PROCESS WATER SYSTEMS,
HEAT TRANSFER SYSTEMS,
AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS,
CONTAINERIZED PONDS AND DECORATIVE FOUNTAINS,
INDUSTRIAL ONCE-THROUGH COOLING WATER SYSTEMS,
WATER TRANSFER LINE SYSTEMS, PULP AND PAPER MILLS,
WASTEWATER SYSTEMS,
OILFIELD APPLICATIONS SUCH AS OIL RECOVERY WELL FLUIDS AND FRACTURING FLUIDS,
SECONDARY OIL RECOVERY SYSTEMS, AND HYDROSTATIC TEST WATERS

CONTROLS BIOFILM DEPOSITS FROM PUMPS, PIPEWORK, HEAT EXCHANGERS, AND FILTERS
ASSOCIATED WITH INDUSTRIAL WATER TREATMENT SYSTEMS AND OILFIELD SYSTEMS

LIMITED DISINFECTION OF ANIMAL, LIVESTOCK AND POULTRY WATER LINES

ACTIVE INGREDIENTS

Sodium bromosulfamate and sodium chlorosulfamate 18%

OTHER INGREDIENTS 82%

TOTAL 100%

Total Halogen (calculated as bromine = approximately 15%)
(calculated as chlorine = approximately 7%)

KEEP OUT OF REACH OF CHILDREN
DANGER/PELIGRO

FIRST AID

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

If swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

See side panel for additional precautionary statements

In case of emergency endangering life or property involving this product, call collect (225) 344-7147

ALBEMARLE CORPORATION
4250 CONGRESS STREET, SUITE 900
CHARLOTTE, NC 28209

EPA Reg. No. 3377-55

EPA Est. 3377-AR-1, 42403-TX-1, 102875-CA-1

Net Contents: _____

Batch number: _____

(Note to reviewer: The following text will be included if more than one EPA Est. No. is listed on the market label.)
Beginning of batch code indicates Est. No.

PRECAUTIONARY STATEMENTS:
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and skin burns. Do not get in eyes, on skin or on clothing. Wear protective eyewear (chemical goggles or face shield), protective clothing and rubber gloves resistant to chemical permeation when handling this product. Harmful if swallowed, or absorbed through the skin. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing separately before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Apply this pesticide only as specified on the label.

PHYSICAL AND CHEMICAL HAZARDS

ALBEMARLE S909 BIOCIDE is not flammable. This product is strongly basic and an oxidizing agent. Avoid contact with organic materials such as alcohols and aldehydes, strong reducing agents, strong oxidizers, acids, and ammonia containing products. In concentrated form, avoid contact with common metals such as steel, aluminum, iron and copper. Use of incompatible materials can promote the exothermic decomposition of the product. In extreme cases, this could result in vigorous gas formation and over-pressurization of storage containers.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

When used as directed, ALBEMARLE S909 BIOCIDE effectively controls bacteria, fungi, algae and slime in commercial and industrial water systems. ALBEMARLE S909 BIOCIDE can also be used to control biofilm deposits from pumps, pipework, heat exchangers, and filters associated with industrial water treatment systems.

ALBEMARLE S909 BIOCIDE may be added at system inlet water or other locations in the system at a point of uniform mixing where the treated water will be circulated or mixed throughout the system. Badly fouled systems should be cleaned before treatment begins. The product may be applied to the system either continuously or intermittently (slug dose) or as needed to obtain the recommended total bromine level. The frequency of feeding and dosage rate will depend upon the severity of the problem.

INITIAL DOSES: When the system is noticeably fouled, apply sufficient ALBEMARLE S909 BIOCIDE to achieve a total bromine level of 4 – 10 ppm or as needed to maintain control. Applying 4 fluid ounces to 1000 gallons of water yields a maximum of 6.4 ppm of total bromine.

SUBSEQUENT DOSES: When microbial control is evident, apply sufficient ALBEMARLE S909 BIOCIDE to achieve a total bromine level of 4 – 10 ppm or as needed to maintain control.

Treatment levels of ALBEMARLE S909 BIOCIDE can best be measured with test kits for either bromine or chlorine. Tests should be made immediately after drawing water samples from the system. Use test kits according to directions. When a bromine test kit is used, results can be read directly as ppm bromine. When a chlorine test kit is used, results can be expressed in terms of bromine by multiplying chlorine values by the conversion factor 2.25.

RECIRCULATING COOLING AND PROCESS WATER SYSTEMS

When used as directed, ALBEMARLE S909 BIOCIDE effectively controls bacteria, fungi, algae and slime in commercial and industrial cooling towers; heat exchange water towers, evaporative condensers, utility plant cooling systems, industrial water scrubbing systems, and influent systems such as flow through filters, lagoons, etc.

HEAT TRANSFER SYSTEMS

For control of bacteria and fungi in heat transfer systems such as hydrostatic sterilizers and retorts, pasteurizers and warmers, and batch and continuous cookers.

AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS

Use only in industrial air washer systems that have mist-eliminating components. For control of microorganisms in industrial air washer or scrubbing systems add sufficient ALBEMARLE S909 BIOCIDE to the air washer sump or chill water. The ALBEMARLE S909 BIOCIDE should be applied to achieve a total bromine level of 4 – 10 ppm or as needed to maintain control. Sampling of the treated systems should be at the bleed-off point and total bromine residuals determined with an appropriate test kit.

Not for use in air washers and industrial scrubbing systems in the State of California.

CONTAINERIZED PONDS AND DECORATIVE FOUNTAINS

ALBEMARLE S909 BIOCIDE may be applied at the pond or fountain inlet or at a location that permits complete diffusion into the water at maximum retention time before reaching the outlet. Sufficient ALBEMARLE S909 BIOCIDE should be fed to maintain a total bromine level of 4 – 10 ppm in all parts of the pond or fountain, or as needed to maintain control.

INDUSTRIAL ONCE-THROUGH COOLING WATER SYSTEMS

When used as directed, ALBEMARLE S909 BIOCIDE effectively controls bacteria, fungi, algae and slime in once-through and closed-cycle fresh and sea water cooling systems. Apply ALBEMARLE S909 BIOCIDE to the system inlet water or before any other contaminated area in the system.

Not for use in industrial once-through heat transfer systems in the State of California.

WATER TRANSFER LINE SYSTEMS

Not for use in food processing equipment, human drinking water systems, or dental lines.

ALBEMARLE S909 BIOCIDE can be used to remove and control biofilm deposits and other organic contaminates in industrial tanks, pumps, piping and tubing associated with water transfer line systems. DOSAGE RATE: Fill water transfer line equipment as completely as possible with a solution of one (1) ounce of product diluted in one (1) gallon of water. Introduce this use solution to the transfer line system. Soak or circulate the use solution for at least 4 hours. Drain the system. Rinse the system thoroughly with potable water prior to using the water transfer lines.

Not for use in water transfer line systems in the State of California.

PULP AND PAPER MILLS

When used as directed, ALBEMARLE S909 BIOCIDE effectively controls algal, bacterial, and fungal slime in pulp and paper mill fresh and sea water influent water systems, cooling water systems, wastewater treatment systems, nonpotable water systems, whitewater systems and other process water. The product may be applied to the system either continuously or intermittently (slug dose) or as needed to obtain the recommended total bromine level.

DOSAGE RATES: Add sufficient ALBEMARLE S909 BIOCIDE to achieve a residual bromine level of 4 – 10 ppm or as needed to maintain control of the system.

Feed ALBEMARLE S909 BIOCIDE directly into the water to be treated. Be sure rapid mixing of the treated water, and ALBEMARLE S909 BIOCIDE is achieved. Pump manufacturers can recommend the appropriate materials of construction and capacity for a pump to feed ALBEMARLE S909 BIOCIDE.

Not for use in pulp and paper mills in the State of California.

WASTEWATER SYSTEMS

When used as directed, ALBEMARLE S909 BIOCIDE controls microorganisms in wastewater systems. The quantity of ALBEMARLE S909 BIOCIDE required varies with the degree of fouling. Add sufficient ALBEMARLE S909 BIOCIDE to achieve residual bromine levels of 3 – 10 ppm, or as needed to maintain control, when measured approximately 5 minutes after treatment. Applying 4 fluid ounces to 1000 gallons of water yields a maximum of 6.4 ppm of total bromine. Higher dosages may be necessary depending upon the system. The product may be applied to the system either continuously or intermittently (slug dose) or as needed to obtain the recommended total bromine level.

Depending on the construction of the wastewater system, ALBEMARLE S909 BIOCIDE may be effectively added to one or more different locations in the system. Frequently the compound is added to wastewater receiving secondary treatment at a contact tank preceding the effluent discharge or at the influent of the final clarifier.

Not for use in wastewater systems in the State of California.

OILFIELD APPLICATIONS

This product is as an algicide, fungicide, and/or slimicide for oilfield applications. It controls biofilm deposits on pumps, pipework, heat exchangers, and filters associated with oilfield systems. It also controls biofilm deposits downhole in formations.

OIL RECOVERY WELL FLUIDS AND FRACTURING FLUIDS

When used as directed, this product will control the growth of bacteria such as anaerobic sulfate-forming bacteria (*Desulfovibrio desulfuricans*) and aerobic slime-forming bacteria (*Bacillus cereus*) which impair the efficiency of well fluids and fracturing fluids.

Add sufficient amount of this product directly to the well fluid or fracturing fluid to achieve a residual bromine level of up to 10 ppm or as needed to maintain control of the system. This product may be added and premixed with the well fluid or fracturing fluid prior to the oilfield operation or may be added directly to the blender during the operation. Be sure rapid mixing of the treated water with this product is achieved.

SECONDARY OIL RECOVERY SYSTEMS

This product may be used in secondary oil recovery water systems, such as oil field water flood or salt water disposal systems for the control of sulfate-reducing bacteria and aerobic slime-forming bacteria, which impair the efficiency of the system.

Add sufficient amount of this product to achieve a residual bromine level of up to 10 ppm or as needed to maintain control of the system. This product can be added whenever needed to maintain 10 ppm residual bromine. Feed this product directly into the water to be treated. Be sure mixing of the treated water with this product is achieved.

HYDROSTATIC TEST WATERS

This product may be used in hydrostatic test water systems for the control of sulfate-reducing bacteria and aerobic slime-forming bacteria, which impair the efficiency of the system and damage pipework by microbially induced corrosion.

Add sufficient amount of this product to achieve a residual bromine level of up to 10 ppm or as needed to maintain control of the system. This product can be added whenever needed to maintain 10 ppm residual bromine. Feed this product directly into the water to be treated. Be sure complete mixing of the treated water with this product is achieved.

Not for use in oilfield applications in the State of California.

CLEAN IN-PLACE LIMITED DISINFECTION OF WATER LINES

This product can be used to disinfect Gram-negative organisms in tanks, pumps or medicators used to deliver the product, piping and tubing associated with water lines in animal, livestock and poultry housing facilities. The water lines can be used for delivering drinking water, air chiller water and cooling spray lines. Prior to use in the water lines, remove all animals, livestock or birds from premises. Do not reintroduce animals, livestock or birds until treatment is complete and water lines have been thoroughly rinsed with potable water.

DOSAGE RATE: Apply the product via a chemical feed pump or medicator at a dose of one (1) ounce of product per one (1) gallon of water [1:128] into the pipes. Fill water lines until the full flow is obtained at all extremities and the system is completely filled with the disinfectant solution and all air is removed. Close drain valves and soak or circulate the disinfectant solution for a minimum of 4 hours. Drain the system. Flush the system thoroughly with potable water prior to using the water lines.

Not for use in water lines in the State of California.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment.

STORAGE: Avoid freezing, excessive heat or exposure to light, especially direct sunlight. If heating is necessary to prevent freezing, care must be taken to prevent overheating. The average product temperature should be maintained below 110°F. Temperature monitoring is recommended. At elevated temperatures, self-heating can lead to vigorous gas generation and over-pressurization of storage containers.

STORAGE CONTAINER: Vented and opaque containers: The product should be stored in vented containers as pressure can build-up in the headspace (nitrogen). To maximize product shelf life, store in opaque containers in a cool, dry, well-ventilated area.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: *[1 - 5 gallon]* Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Offer for reconditioning if appropriate. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

CONTAINER DISPOSAL: *[15, 30 and 55 gallon drums]* Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Offer for reconditioning if appropriate.

Triple rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

CONTAINER DISPOSAL: *[275-300 gallon tote or IBC]* Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Offer for reconditioning if appropriate.

Triple rinse as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times.

ALBEMARLE S909 Biocide label

[The following statement will be used on labels for tank trucks]

Do not rinse or clean the tank after unloading the contents. Release the tank truck for return to Albemarle Corporation.

[The following statements will be used on labels for stationary tanks]

Refillable container. Refill this container with like pesticide products. Do not reuse this container for any other purpose.

CONTAINER DISPOSAL: Cleaning the container before final disposal is the responsibility of the person disposing of the container. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times.

[the following HMIS and NFPA ratings are optional and may or may not appear on the label]

HMIS Health 3 Flammability 0 Physical Hazards 0

NFPA Health 3 Flammability 0 Instability 0 Physical Hazards -

OPTIONAL GRAPHICS:

Kosher Symbol:

(U)

 ALBEMARLE®

Sales and service by:

PASSPORT
Food Safety Solutions powered by 

6935 Vista Drive, West Des Moines, IA 50266

Phone 515.334.8035 Web passportfoodsafety.com