

## **DIRECTIONS FOR USE**

Algicil is used to kill and control the growth of algae, including so called 'black algae' swimming pools. For maximum effectiveness, pools containing heavy growth of algae should be cleaned prior to using Algicil. For pools having visible growth of algae, add an initial dose of 12-18 oz. of Algicil per 10,000 gal. water (approx. 11/2 oz. to 1000 gal.) and remove settled algae debris by cleaning (vacuuming). For treatment of freshly cleaned and filled pool, add initial dose 7-12 oz. of Algicii per 10,000 gal. pool water (approx. 1 oz. per 1000 gal.) To maintain pools free of visible algae growth, subsequent additions of 214 oz. Algicil per 10,000 gal (approx. 1 oz. per 5000 gal.) should be every 5-7 days after initial treatment. Uniform distribution (pour all around pool) of Algicil throughout the pool water is necessary for maximum effectiveness.

Algicil is compatible with those chemicals normally used to treat pools and is effective at both acid and alkaline pH. Algicil can be used in pools treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, co not mix Algicil with concentrated dry or liquid colorine products.



## **BLACK AND MUSTARD ALBAE**

- No Foaming
   No Discoloration
- No Staining
- No Metals

Active Ingredient: Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene 

Inert ingredient . . . .

KEEP OUT OF REACH OF CHILDREN

Side side panel for further cautions E.P.A. Reg. No. 3432-42 E.P.A. EST. No. 3432-PA-1

NET CONT: 1 GAL. (3.785 Liter)

CAUTION: KEEP OUT F REACH OF CHILDREN!
Harmful if swallowed. Do not get in eyes. Avoid
contact with skin. In case of contact, flush with
plenty of water for at least 15 minutes. If eye
irritation persists get andical attention. Avoid contamination of food. Rinse empty container thoroughly with water and discard container. This product is toxic to fish. Treated effluent should not be discharged where it will drain into takes, streams, ponds, or public water. Apply this product only as specified on this label.

To Calculate Capacity of Pool Rectangular Pools: Multiply length of pool x width of pool x average depth (all in feet)  $\times$  7.5 =

gailons. Round Pools: Multiply diameter of pool x

diameter of pool x average depth (all in feet) x 5.9 = ga!lons.

THE PROFESSIONAL FAMILY OF PROBLEM SOLVERS

AQUA-POL: For clear sparkling water.
KEETROL: Protects against stains, rust, corrosion.
OXY-KLEER: A "super" oxidizing agent.
THERMATROL: Reduces heat loss and water evaporation. LUSTRE-ALL: Instant cleaner for tile, vinyi, and chrome. ALGITEC 50: A concentrate for general algae protection. ALGICIL: For effective green and black algae control. FILTER-RENU: A cleaning agent for filters.

Repackaged by n. jonas & Co., inc. BENSALEM, PA. 19020