



Front Panel

ACCEPTED
JUN 13 1984
JUN 3 1984
for the Federal Insecticide,
Fungicide, and Rodenticide Act
Registered under 3468-3

PENTA WOOD PRESERVATIVE
Ready-to-Use Wood Preservative

Active Ingredients:	
Pentachlorophenol	4.25%
Other Chlorophenols and Related Compounds	0.75%
Inert Ingredients:	95.00%

Keep Out of Reach of Children (12 pt)

DANGER (18 pt)

Statement of Practical Treatment

For Eyes: In case of contact with eyes, flush with plenty of water for at least 15 minutes. Call a physician.

For Skin: Wash exposed areas of skin with soap and water after handling or using.

If Swallowed: Do not induce vomiting. Call a physician immediately.

Note: Remove and wash contaminated clothing before reuse or discard in accordance with instructions for pesticide container disposal.

See Side Panel for Additional Precautionary Statements

EPA Reg. No. 3480-4

EPA Est. No. 3480-WA-1

Net Contents: 1 gallon

American Lat Company
Seattle, WA 98104

BEST DOCUMENT AVAILABLE

Side Panel

Precautionary Statements
Hazards to Humans and
Domestic Animals

DANGER

(18 pt)

Corrosive: Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield when handling. Harmful or fatal if swallowed. Avoid contamination of food or feed.

Environmental Hazards

This product is toxic to fish and wildlife. Do not apply directly to water or wetlands. Do not contaminate water by cleaning of equipment or disposal of wastes.

Physical and Chemical Hazards

Contains petroleum distillate. Do not use, pour, spill or store near heat or open flame.

Notes on Handling: Because this product contains petroleum distillate, proper precaution should be taken to insure adequate ventilation. It should not be applied in the presence of open flames. Smoking during application should not be permitted in the area. All eating and drinking should be prohibited when treating millwork. Suitable work clothing, rubber gloves and safety glasses should be worn during application.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Storage and Disposal

(12 pt)

Do not contaminate water, food, or feed by storage or disposal.

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or mixture is a violation of Federal law. If these wastes cannot be disposed of by the according to label instructions, contact your State Pesticide or Environmental Control Agency, or the nearest waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

BEST DOCUMENT AVAILABLE

Side Panel (Cont)

Instructions for Application

Uses: ATCO #1405 Penta Wood Preservative is a clean, clear and nearly odorless pentachlorophenol liquid treatment for use on all exterior wood exposed to moisture or soil. It saturates deep into wood to combat dry rot, mildew, mold, fungus, termites, ants, and wood beetles. It can be painted over (except with water base stains), and protects the paint against peeling and blistering. ATCO #1405 Penta is insoluble in water. It can be used on wood shake and wood shingle roofs to resist moss growth and can be used to kill moss on brickwork. ATCO #1405 Penta can be pigmented with oil colors to make custom stains. Treated wood will normally last 5-8 years longer than untreated wood.

Directions: Wood to be treated should be dry, seasoned and free of bark and foreign matter for best results. Whenever practical, wood should be dipped into ATCO #1405 Penta. Lumber should be immersed at least 3 minutes. Dip fence posts for 24-48 hours and pour Penta into the fill dirt as it is replaced around the post. Use about 1/2 gallon of Penta for each cubic foot of wood. If a brush-on method is used, get as much Penta on the wood as possible without excessive run-off. Let dry and apply another heavy coat. Use one gallon for 150-250 square feet.

WARRANTY: If you open this container and find that the product does not conform to the specifications on the label or in our catalog, you may return it within 20 days of purchase to American Tar Company (ATCO) at 1700 N. Northlake Way, Seattle, WA 98103, and ATCO will promptly replace it without charge. This is in lieu of all other warranties, either express, implied and or statutory, and except for this warranty, all express, implied, and statutory warranties (including the implied warranties of merchantability and fitness for a particular purpose) are hereby disclaimed. Replacement is your only remedy and ATCO's only liability. ATCO shall not be responsible for any damage of any kind associated with the use of this product or any damage of any kind resulting from its use. (Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you). This warranty does not create a right, and you may also have other rights which vary from state to state.

BEST DOCUMENT AVAILABLE