

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

Do not contaminate water by cleaning of equipment or disposal of wastes.

GLOUCESTER SEA JACKET® ANTIFOULING PAINT FOR UNDERWATER RUNNING GEAR

ACTIVE INGREDIENT	
Tributyltin Fluoride	9.88%
INERT INGREDIENTS	90.12
	100.00%

WARNING KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL CAUTIONS

560 NEUTRAL GRAY

1/2 PINT U.S. MEASURE

ACCEPTED
JUL 22 1974
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
EPA ECONOMIC POISON REGISTER
UNDER NO. 282-36 SUBJECT
TO ATTACHED COMMENTS.

EPA Reg. 3432-36
EPA Est. 7995-MA1

This is a hard, tightly adhering paint formulated especially for prevention of fouling on underwater running gear such as struts, rudder, propeller and lower units of outboard or inboard engines used in salt water. Its neutral gray color will blend harmoniously with practically every engine. Do not use it in any household application. Not for use on wood.

DIRECTIONS FOR USE

Surface to be painted must be scrupulously clean. Remove all old paint and previous corrosion by sanding to bright metal. Wash with 551 thinner to remove oil and salt. Stir paint thoroughly before using. Apply at least 2 coats by brush directly to the surface; no primer necessary, as it will not cause corrosion. Allow at least 2 hours between coats and before immersing. Use 551 thinner for thinning only if necessary, and for cleaning brushes.

WARNING: FLAMMABLE. Do not use, pour, spill or store near heat or open flame. May be fatal if swallowed. Causes severe eye burns. May cause skin irritation. Do not get in eyes, on skin or on clothing. Wash immediately with soap and water in case of skin contact. Flush eyes with clear water. Wash contaminated clothing before reuse. Wear face shield or goggles. Keep container closed when not in use. Keep out of reach of children. Use with adequate ventilation.

GLOUCESTER PAINTS, INC.
GLOUCESTER, MASS. 01930