

	INGREDIENT:
Trichlo	ro-s-triazinetrione
OTHER	INGREDIENTS
	TOTAL 100.0%
	Available Chlorine
	KEEP OUT OF REACH OF CHILDREN
	DANGER
	FIRST AID STATEMENT
IF SWALLOWED:	Call a poison control or doctor immediately for treatment advice. Have person sip glass of water if able to swallow. Do not induce vorniling unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF IN EYËS:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF OL: SKIN OR CLO: LING:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
IF INHALED:	Move person to fresh air. If person is not breathing, call 911 or an ambutance, then give artificial respiration, preferably mouth to mouth if possible. Call a porson control center or doctor for further resument advice.
HOT LIÑE NUMBER:	Have the product container or label with you when calling the poison control center or doctor, or going for treatment. You may also contact 973-473-1222 for further questions
NOTE TO PHYSICIAN:	Probable mucosal damage may contraindicate the use of gastric lavage.

ACCEPTED FEB 5 2002 (This function of angroude and Nov 3595-38

Net Weight: 4 lbs. (1.814 kg)

a

3525-38

The Universal Replacement Cartridge controls the growth of bacteria and algae in swimming pools. It consistently releases a pre-measured dose to eliminate the need for measuring and handling chemicals. The Universal Replacement Cartridge will fit E-Z Chlor Feeders. Guardex T300 & T400 Feeders, Tabex Aquarian Feeders, Sylvan Skimmer Feeders, AnthoPure T100 Feeders, Guardex, most float rings and more. DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Reentry into treated swimming pools/spas is prohibited above levels of 3.0 ppm.

1. Check the pH of the pool water with a test kit and adjust as necessary to maintain a pH range of 7.2 to 7.6. 2. Add Chlorine Stabilizer or an equivalent product containing cyanuric acid if the pool has not been stabilized previously.

3. Superchlorinate newly filled pools or pools with no chlorine residual with a shock treatment, following all label directions. NOTE: Do not enter pool until the chlorine residual has dropped to 2.0 ppm (parts per million). 4. Punch out holes marked "1" and "2" on the sides of this cartridge. Then punch out additional holes until a satisfactory chlorine residual is reached. As more holes are punched, the chlorine residual will rise.

5. It is recommended that the pH and chlorine levels be checked daily with a test kit to maintain a pH level of 7.2 to 7.6 and a chlorine residual of 1.0 to 1.5 ppm.

6. When cartridge is empty, replace it immediately. The Universal Replacement Cartridge is designed to be used in automatic chlorinators, floating dispensers and other types of flow thru proportioning devices. In certain pools, the cartridge may be placed in the skimmer and scrowed into the skir mer cover. Follow the equipment manufacturer's directions to insure a constant chlorine residual of 1.0 to 2.0 pom. IMPORTANT: Do not remove tablets from cartridge or refill when empty. If the cartridge is placed in the skimmer, do not add other chemicals to the skimmer. Do not mix this product with other chemicals.

PRECAUTIONARY STATEMENTS Hazards To Humane And Domnstic Animals

DANGFR: Kerp Out Of Brach Of Children. CORRO-SIVE. Caus es treversible cive damage and skin burns. May be fatul if absorbed through skin. May be fatal if inhaled, Do not breathe dust or spray mists. Irritating to nose and throat, Harmful it swallowed. Do not get in eyes, on skin or on clothing. Wear goggles or face shield, protective clothing and rubber gloves when handling this product. Wash thoroughly with soap and water after handling and before eating, drinking or using to-bacco. Remove contaminated clothing and wish before reuse

PHYSICAL AND CHEMICAL HAZARDS

STRONG OXIDIZING AGENT. Mix only with water Use clean, dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire and explosion. Contamination with moisture, organic matter, or other chemicals may start a chemical reaction with generation of fire and explosion. In case of contamination or decomposition, do not reseal container, Isolate container, if possible, in open air or well ventilated area. Flood with large volumes of water to dissolve all materials before discarding this container

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and other aquatic organism. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Keep this product dry in a tightly closed container when not in use. Store in a cool, dry, well ventilated area away from heat and open flame. In case of decomposition, do not reseal container. Isolate container, if possible, in open air or well ventilated area. Flood with large volumes of water to dissolve all material before discarding container. Do not reuse empty container, but place in trash collection. Do not contaminate food or feed by storage, disposal or cleaning of equipment. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. EPA Reg. No. 3525-38

EPA Est. No. 3525-NJ-1 44551 S44551 Manufactured by:



Passaic, NJ 07055