

26 JAN. 1978
3525-65

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

PRACTICAL TREATMENT (FIRST AID): If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

Utikem

WTC-#100

ALGAE CONTROL

For control of algae, bacteria, and fungi
in recirculating water cooling towers.

- Non-foaming
- Effective in Hard Water

ACTIVE INGREDIENT:

Poly [oxyethylene (dimethyliminio) ethylene
(dimethyliminio) ethylene dichloride] 15.0

INERT INGREDIENT 85.0

This product contains 1.29 lb. of active ingredient per gallon
and weighs 8.58 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN
CAUTION:**

See additional precautions and First Aid on side panel.

Manufactured by
UTILITY CHEMICAL COMPANY
Sixth Avenue and Wait Street, Paterson, New Jersey 07524
NET CONTENTS: 1 Gal. (128 fl. oz./ 3.8 L)

EPA REG. NO. 35251

Utikem

WTC-#100

ALGAE CONTROL

For control of algae, bacteria, and fungi in recirculating water cooling towers.

- Non-foaming
- Effective in Hard Water

ACTIVE INGREDIENT

Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloride] 15.0

INERT INGREDIENT 85.0

This product contains 1.29 lbs. of active ingredient per gallon and weighs 8.58 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION:

See additional precaution and first aid information on label.

Manufactured by

UTILITY CHEMICAL COMPANY

Sixth Avenue and Wait Street, Paterson, New Jersey 07524

NET CONTENTS 1 Gal (128 fl oz) 3.8 L

DIRECTIONS FOR USE GENERAL CLASSIFICATION

Utikem WTC-#100 is a non-foaming, non-toxic, non-corrosive, non-oxidizing, non-flammable, and non-hazardous liquid. It is used to control algae, bacteria, and fungi in recirculating water cooling towers and industrial water systems. Proper application systems must be used to insure uniform distribution and avoid deposits.

An initial addition of 10 to 100 fluid ounces of UTIKEM WTC-#100 ALGAE CONTROL per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of UTIKEM WTC-#100 ALGAE CONTROL based on the total weight of water in the system is recommended. Repeat this dosage until control is achieved.

Subsequent additions of 10 to 100 fluid ounces of 32 to 80 parts per million of UTIKEM WTC-#100 ALGAE CONTROL should be made every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of feed and the severity of the algae problem. Feed additional quantities as needed to insure control of algae in recirculating water cooling towers.

STORAGE & DISPOSAL Keep container closed when not in use. Do not contaminate water, food, or feed by storage or disposal. Rinse container if empty. Do not reuse empty container. Triple rinse of empty container and dispose of container in an approved manner and place in a safe place. Rinse that cannot be reused or recycled should be disposed of in a safe place. Do not store in a safe place away from children and pets.