

OXFORD® BRYTE-FOAM

Concentrated, Sanitizer, Rug and Upholstery Cleaner

DIRECTIONS

Carpets, Hospital and Institutional: The material to be cleaned should be tested for colorfastness.

First, vacuum carpet to remove loose soils. Then remove grease and oil spots. Other stains should also be removed with a suitable spotting compound. To clean and sanitize carpets, prepare a solution of 1 part BRYTE-FOAM to 20 parts of warm water (1 quart of BRYTE-FOAM to 5 gallons of water) or 1 part BRYTE-FOAM to 16 parts water if carpet is heavily soiled (8 ounces BRYTE-FOAM to 1 gallon of water). Place solution in reservoir tank of carpet shampooing machine. Use 1 to 1½ gallons of diluted cleaner for each 120 sq. ft. of carpet to be cleaned and sanitized. Adjust stopcock on tube leading from reservoir tank into brush head of machine so that a sufficient amount of solution will be deposited on the rug which will produce a copious dry foam as the brush of the machine travels over the moistened surface of the carpet. Guide the machine over the carpet using a circular motion (left to right and then right to left with a slight overlap working the solution into the fibers of carpet all the way across the carpet. After scrubbing, pick up excess moisture and residues with a wet and dry vacuum machine. Brush in one direction for proper drying and elimination of shading. NOTE: When using a fibre brush, wet with water soften before using.

L-72

• Cleans • Revitalizes • Brightens • Deodorizes •
Sanitizes • Retards Soiling • Soapless • Non-Flammable

ACTIVE INGREDIENTS: Sodium Lauryl Sulfate, 9.000%;
Sodium Dodecylbenzene Sulfonate, 8.120%; Sodium
o-benzyl p-chlorophenate, 1.238%

INERT INGREDIENTS81.642%

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with eyes. In case of contact, flush thoroughly with water. If irritation persists, get medical attention. Avoid contact with skin. Rinse empty container and discard it.

EPA Reg. No. 3635-174

Net Contents _____ Gallons

Pre-soak is not required when the proper nylon brush is used. Replace furniture, and equipment when carpet is dry. If carpet is not completely dry when furniture and equipment are replaced, place wax paper or aluminum foil under legs to avoid indentations and rust marks on carpet.

CARPETS, NON HOSPITAL USE: For new type upright Dry Foam carpet shampooing machine, dilute one part BRYTE-FOAM to 8 parts of water. Use method and procedures as described in manufacturers manual for this type of carpet shampoo machine.

Upholstery: Pretest material for colorfastness. If a special hand shampooing machine is used for cleaning and sanitizing upholstery, follow same general directions as under Carpets. To clean and sanitize upholstery by hand, first prepare a solution of 1 part BRYTE-FOAM to 12 parts warm water (10-2/3 ounces BRYTE-FOAM per gallon of water). Agitate solution vigorously to obtain heavy suds. Then saturate a sponge with the suds and clean the fabric thoroughly. Only use suds—do not wet fabric.

PRS-4A

OXFORD
CHEMICALS

T.M.



A CONSOLIDATED FOODS COMPANY
RESPONSIVE TO CONSUMER NEEDS

© 1972 CONSOLIDATED FOODS CORPORATION
ALL RIGHTS RESERVED

P.O. BOX 80202 ATLANTA, GEORGIA 30341