

INSTRUCTIONS FOR USE:

BULK TANK CLEANING

1. The pick-up tank truck driver should rinse out the tank at the time of pick-up with tepid water.

2. Make certain the compressor is turned off.

3. Remove all dirt and debris which may make cleaning difficult.

4. Add 100 lbs. of BULK TANK CLEANER to 1000 gallons of water.

5. Spray the solution over the tank surfaces.

6. Allow the solution to remain on the tank surfaces for 15 minutes.

7. Rinse the tank with water.

8. Repeat steps 4 through 7 until the tank is clean.

9. Rinse the tank with water.

10. Repeat steps 4 through 7 until the tank is clean.

11. Rinse the tank with water.

12. Repeat steps 4 through 7 until the tank is clean.

13. Rinse the tank with water.

14. Repeat steps 4 through 7 until the tank is clean.

15. Rinse the tank with water.

16. Repeat steps 4 through 7 until the tank is clean.

17. Rinse the tank with water.

18. Repeat steps 4 through 7 until the tank is clean.

19. Rinse the tank with water.

20. Repeat steps 4 through 7 until the tank is clean.

21. Rinse the tank with water.

22. Repeat steps 4 through 7 until the tank is clean.

UBBER WASH

ANITIZER

1. Immediately following the use, pre-rinse with tepid water.

2. Begin cleaning using BULK TANK CLEANER according to its label at a temperature as warm as the hand can stand. Brush all surfaces.

3. Twice each week follow the above with a solution of MOLD REMOVER at the rate of 1 lb. per 100 gal. of water at 145° F. for 15 minutes.

4. Rinse the tank with water at 145° F. for 15 minutes.

5. Wash the tank with UBBER WASH ANITIZER at the rate of 1 oz. to 8 gal. of water (100 ppm) at a temperature of 145° F. for 15 minutes.

6. Rinse the tank with potable water.

7. Repeat steps 4 through 6 until the tank is clean.

8. Rinse the tank with water.

9. Repeat steps 4 through 6 until the tank is clean.

10. Rinse the tank with water.

11. Repeat steps 4 through 6 until the tank is clean.

12. Rinse the tank with water.

13. Repeat steps 4 through 6 until the tank is clean.

14. Rinse the tank with water.

15. Repeat steps 4 through 6 until the tank is clean.

16. Rinse the tank with water.

17. Repeat steps 4 through 6 until the tank is clean.

18. Rinse the tank with water.

19. Repeat steps 4 through 6 until the tank is clean.

20. Rinse the tank with water.

INSTRUCTIONS FOR UTENSILS & OTHER DAIRY EQUIPMENT:

1. Immediately following the use, pre-rinse with tepid water.

2. Begin cleaning using BULK TANK CLEANER according to its label at a temperature as warm as the hand can stand. Brush all surfaces.

3. Twice each week follow the above with a solution of MOLD REMOVER at the rate of 1 lb. per 100 gal. of water at 145° F. for 15 minutes.

4. Rinse the tank with water at 145° F. for 15 minutes.

5. Wash the tank with UBBER WASH ANITIZER at the rate of 1 oz. to 8 gal. of water (100 ppm) at a temperature of 145° F. for 15 minutes.

6. Rinse the tank with potable water.

7. Repeat steps 4 through 6 until the tank is clean.

8. Rinse the tank with water.

9. Repeat steps 4 through 6 until the tank is clean.

10. Rinse the tank with water.

11. Repeat steps 4 through 6 until the tank is clean.

12. Rinse the tank with water.

13. Repeat steps 4 through 6 until the tank is clean.

14. Rinse the tank with water.

15. Repeat steps 4 through 6 until the tank is clean.

16. Rinse the tank with water.

17. Repeat steps 4 through 6 until the tank is clean.

18. Rinse the tank with water.

19. Repeat steps 4 through 6 until the tank is clean.

20. Rinse the tank with water.

21. Repeat steps 4 through 6 until the tank is clean.

22. Rinse the tank with water.

23. Repeat steps 4 through 6 until the tank is clean.

24. Rinse the tank with water.

25. Repeat steps 4 through 6 until the tank is clean.

*Prepared by
Borden Chemical*