

### **CAUTION! KEEP OUT**

OF THE REACH **OF CHILDREN** 

# 9150 Wormicide

See other precautions on the back/side panel.

9150 WORMICIDE

**Active Ingredients:** Tributyltin Oxide Inert Ingredients:

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

## MANUFACTURED BY THE DOLPHIN PAINT & CHEMICAL COMPANY TUGEOU : OHIO OFS A

2.00%

**98**.00% 100.00%

# DO IT RIGHT - WITH Dolfinite

#### 9150 WORMICIDE

Wormicide is unique in that it penetrates the wood rather than seals it. It carries its protective ingredients deep into the pores, thereby adding years to the life of the boat. This clear water white solution is especially formulated for application to both the exterior and interior of hulls to provide protection from teredos, worms and other marine borers. It should be applied prior to the finishing. Wormicide has no effect or the finish coat.

DIRECTIONS-EXTERIOR HULL. Apply a liberal coat with a brush to new wood, or old wood where all paint has been removed. Allow at least 1 hour drying time before painting.

INTERIOR HULL APPLICATION FOR **PREVENTION OF DRY ROT.** The solution should be reduced by the ratio of 3 parts mineral spirits to 1 part 9150 Wormicide before application. Then apply a liberal coat of the reduced solution and allow at least 1 hour drying time before painting.

CAUTION: CONTAINS TBTO (Bis-Tri-N-Butyl tin Oxide) AND PETROLEUM DISTILLATE. Harmful if swallowed. Do not induce vomiting. Call physician immediately. May be absorbed through skin. Causes skin irritation. Avoid contact with skin, eyes or clothing. In case of contact, immediately remove contaminated clothing and wash skin with soap and water; for eyes, flush with plenty of water and get medical attention. Wash clothing before reuse. Do not use near heat, sparks or open flame. Use with adequate ventilation. Close container after each use. Avoid storage near feed and food products.

#### QUALITY PRODUCTS SINCE 1885