

QUALITY PRODUCTS SINCE 1885



Dolfinite 3431-TX is a heavy bodied compound with fungicidal ingredient for waterproofing and sealing double planked construction of wood boats, either with or without canvas.

ADVANTAGES: Preserves wood, seals all worm holes and joints and remains flexible throughout the life of the boat. Not affected by atmospheric changes, it will not become soft and ooze in warm temperatures or become hard and brittle in cold temperatures. Brown in color. Will not bleed through paint.

THINNING: Use Dolfinite Thinner No. 1481-TX if needed.

APPLICATION: May be applied by brush, spray or trowel. On double planked bottoms where no canvas is used, No. 3431-TX should be applied in full consistency to fill, waterproof and seal all voids.

When used for waterproofing double planked bottoms with canvas No. 3431-TX should be thinned if necessary and brushed or sprayed on the short or diagonal planking, canvas attached, and a coat of No. 3431-TX applied over the canvas. Outer planking is then put in place over the coated canvas.

WARNING: CONTAINS XYLOL, PENTACHLOROPHENOL AND PETROLEUM DISTILLATE.

Keep away from heat, sparks and open flame. Avoid contact with skin and breathing of vapor. Contaminated shoes and clothing should be removed promptly and skin thoroughly washed with soap and water. Use with adequate ventilation. Close container after each use.

ANTIDOTE: If swallowed, DO NOT induce vomiting. Call physician immediately.

IF ON SKIN: In case of contact, immediately wash skin with soap and water.

EYES: For eyes, flush with plenty of water for at least 15 minutes and get medical treatment.

U.S.D.A. Registration No. 3658-26

DO IT RIGHT - WITH *Dolfinite* "