

★ ★ ONE U.S. STANDARD GALLON

IMPERIAL MEAS. 132 FL. OZ. ★ ★ ★

DOLFINITE



WARNING!
COMBUSTIBLE!
KEEP OUT OF REACH
OF CHILDREN

See back panel for
additional required
Caution Statements

9145 Double Duty Anti-Fouling

NET CONT. 128 FL. OZS. (1 GAL.)

9145 DOUBLE DUTY RED ANTI-FOULING	
Active Ingredients:	29.98%
Cuprous Oxide	12.75%
Pine Tar	17.23%
Inert Ingredients:	70.02%
	100.00%
Pigment:	51.20%
Magnesium Silicate	25.65%
Cuprous Oxide	12.75%
Iron Oxide	10.75%
Diatomaceous Silica	2.05%
Vehicle:	25.00%
Pine Tar	17.23%
Hardened Rosin	7.77%
Volatile:	23.80%
Petroleum Thinners	23.80%
(Copper as Metallic — 11.3%)	

3658-23

July 19, 1971

MANUFACTURED BY THE DOLPHIN PAINT & CHEMICAL COMPANY TOLEDO 3, OHIO, U.S.A.

★ ★ QUALITY PRODUCTS SINCE 1885 ★

DOLFINITE 9145 DOUBLE DUTY RED ANTI-FOULING

DOLFINITE 9145 DOUBLE DUTY RED ANTI-FOULING has been formulated to provide boat owners a tough, serviceable bottom paint with good protective characteristics. It is easily applied, straight from the can, by brush, roller or spray. Dries to a deep reddish-brown flat finish. Requires overnight drying. Boat should be launched within 24 hours after application of last coat. Surface should be clean, dry and free of any loose paint, scale or other foreign matter. All worn or bare spots should be touched up prior to application of first coat. Shake thoroughly and stir frequently to insure thorough distribution of protective ingredients. Two coats recommended.

WOOD BOATS: No undercoater required. Apply material as received by either brush, roller or spray. Only turpentine should be used for thinning.

FIBERGLASS: Thoroughly and carefully sand hull with a medium course sand paper and wipe clean with Dolfinite 1001 thinner before application.

STEEL AND ALUMINUM: Application to metal hulls requires a complete system of galvanic and or electrolysis barrier coats. Ask your dealer for the instruction booklet covering preparation of steel and aluminum hulls.

CAUTION: CONTAINS COPPER AND PETROLEUM DISTILLATE. Harmful if swallowed. Keep away from heat, sparks and open flame. Avoid prolonged contact with skin and breathing of vapor and spray mist. In case of prolonged contact, immediately wash skin with soap and warm water. Use with adequate ventilation. Close container after each use. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

KEEP OUT OF THE REACH OF CHILDREN

U.S.D.A. Registration No. 3658-33

3658-33

July 19, 1971

U.S.A.

DO IT RIGHT - WITH *Dolfinite*