

41
WTT
COMPOSITION

Percent by weight

Active Ingredient	10.0%
Poly[oxyethylene(dimethyliminio)ethylene(dimethyliminio)-	
ethylene dichloride]	10.0%
Inert Ingredient	90.0%
Weight per gallon	8.49 pounds
Weight of active ingredient per gallon....	0.85 pound

EPA Reg. No. 3837-41
EPA EST NO. 3837-MO-1

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not discharge treated effluent where it will drain into lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

MANUFACTURED BY

LUBAR COMPANY

1708 Campbell

Kansas City, Missouri 64108

ACCEPTED

NOV 7 1974

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER-
ED UNDER NO. 3837-41 SUBJECT
TO ATTACHED COMMENTS.

3837-4

APPLICATION

WTT is used to control algae, bacteria, and
lating commercial and industrial water cooling
its use, systems must be cleaned to remove al
biological slime and other deposits. An initia
6.13 to 15.32 fluid ounces of WTT per 1000
to provide a concentration of 48 to 120 pp
WTT based on the total weight of water
recommended. Repeat initial dosage until
Subsequent slug additions of 1.53 to 15.32 fl
per 1000 gallons of water (12 to 120 parts p
should be employed every 2 to 5 days a
frequency of addition depends upon the r
bleedoff and the severity of the microbiolog
additions should be made in the sump of wa

ACCEPTED

NOV 7 1974

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER-
ED UNDER NO. 31274 SUBJECT
TO ATTACHED COMMENTS.

3837-41

3837-41

Percent by weight

10.0%

ne(dimethyliminio)-

10.0%

90.0%

8.49 pounds

lon.... 0.85 pound

41

D-1

F CHILDREN

es. Avoid contact with
lenty of water for at
sts, get medical atten-

scharge treated effluent
s, or ponds. Do not
ipment or disposal of

drum reconditioner or
burying in a safe place.

Y

PANY

City, Missouri 64108

APPLICATION

WTT is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of WTT per 1000 gallons of water to provide a concentration of 48 to 120 parts per million of WTT based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.53 to 15.32 fluid ounces of WTT per 1000 gallons of water (12 to 120 parts per million of WTT) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.