

BETZ®

C-5P

WARNING—TOXIC—HARM
material dry. If material gets wet, it may
chlorine gas. Avoid inhalation. Causes s
eyes, on skin or clothing. Wear rubber
shield, when handling. In case of conte
soap and water. In case of contact wi
thoroughly with water. In case of inges
inhalation of chlorine gas, secure immed
Do not reuse empty container. Send to d
by perforating or crushing and bury in a

DIRECTIONS FOR USE—
of fungi and bacteria in the water in br
circulating industrial water cooling tower
This product should be used at a rate b
per thousand gallons of water per comp
ery pasteurizers and between 0.2 and
lons of water contained in a recircula
system. Measurement of the residual c
should be made on a periodic basis to
million (ppm) residual minimum. Repea
needed. In the event the system is l
recommended.

FOR INDUSTRIAL USE ONLY. Technical
problems is available from BETZ.

STORE IN COOL

BETZ LABO

WARNING—TOXIC—HARMFUL IF SWALLOWED. Keep material dry. If material gets wet, it may decompose, liberating toxic chlorine gas. Avoid inhalation. Causes skin irritation. Do not get into eyes, on skin or clothing. Wear rubber gloves, and goggles or face shield, when handling. In case of contact with skin, wash well with soap and water. In case of contact with eyes, flush promptly and thoroughly with water. In case of ingestion or contact with eyes or inhalation of chlorine gas, secure immediate medical attention.

Do not reuse empty container. Send to drum reconditioner, or destroy by perforating or crushing and bury in a safe place.

DIRECTIONS FOR USE—Betz C-5P aids in the control of fungi and bacteria in the water in brewery pasteurizers and in recirculating industrial water cooling towers.

This product should be used at a rate between 0.1 and 0.75 pound per thousand gallons of water per compartment in the case of brewery pasteurizers and between 0.2 and 1.0 pound per thousand gallons of water contained in a recirculating industrial water cooling system. Measurement of the residual chlorine levels in the systems should be made on a periodic basis to insure a 0.2 to 0.5 part per million (ppm) residual minimum. Repeat treatment every day, or as needed. In the event the system is badly fouled, precleaning is recommended.

FOR INDUSTRIAL USE ONLY. Technical advice regarding specific site problems is available from BETZ.

STORE IN COOL DRY PLACE—KEEP CONTAINER COVERED

BETZ[®]

LABORATORIES, INC. / TREVOSE, PENNSYLVANIA

ACCEPTED

7-6-72

3876-18

Contents: PELLETS

Active Ingredients:

1, 3-dichloro-5,
5-dimethylhydantoin 48%

Inert Ingredients* 52%

*Inert ingredients include solubilizing
and dispersing agents.

EPA Reg. No. 3876-18

NET WEIGHT

As Marked on Container