

131174 slimicide C-68
 REDUCES MICROBIAL GROWTH IN INDUSTRIAL
 WATER COOLING TOWERS AND AIR WASHING SYSTEMS

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER
 CORROSIVE. CAUSES EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED. MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.
 Do not get in eyes, on skin or clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.
ENVIRONMENTAL HAZARDS
 This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on the label.
DIRECTIONS FOR USE
 It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL
STORAGE Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. If plastic, do not reuse empty container.
DISPOSAL Pesticide or rinsate that cannot be used or chemically repackaged should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Triple rinse for equipment all containers and, for metal containers, offer for recycling or reconditioning (for plastic containers dispose in an incinerator) or dispose in a landfill approved for pesticide containers or bury in a safe place. Consult Federal, state or local disposal authorities for approved alternate procedures.
 (Directions for use continued on right panel)

Contents LIQUID

Active Ingredients	
3-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
Inert Ingredients	98.50%
Total	100.00%

These ingredients include stabilizing and dispersing agents.

EPA Reg. No. 597-109
 WEIGHT PER GALLON OF PRODUCT: 8.4 Pounds
 NET WEIGHT OR VOLUME AS MARKED ON CONTAINER

KEEP OUT OF REACH OF CHILDREN
DANGER
STATEMENT OF PRACTICAL TREATMENT
 In case of contact with skin, wash immediately with plenty of soap and water. Immediately consult physician.
 In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes. Immediately consult physician.
 In case of inhalation, remove affected person from contaminated area to fresh air. Immediately consult physician.
 In case of ingestion, immediately contact physician.
 A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.

INDUSTRIAL RECIRCULATING COOLING WATER SYSTEMS
 For the control of bacteria, algae and fungi in evaporative condensers, heat exchange water systems, cooling towers and industrial cooling towers, industrial water circulating systems and brewery pasteurizers. Add Slimicide C-68 to the tower basin, distribution line or some other point to insure uniform mixing.
INITIAL DOSE When the system is noticeably fouled, apply 148 to 883 ppm Slimicide C-68 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of 5-micron C-68 per 1000 gallons of water in the system). Repeat until control is achieved.
SUBSEQUENT DOSE When microbial control is evident, add 35 to 219 ppm Slimicide C-68 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of 5-micron C-68 per 1000 gallons of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.
AIR WASHER SYSTEMS
 Add to the air washer sump or sump water pump, to insure uniform mixing, 35 to 883 ppm Slimicide C-68 (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of Slimicide C-68 per 1000 gallons of water in the system) depending upon the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.
INTERMITTENT OR SLOW METHOD
INITIAL DOSE When the system is noticeably fouled, apply 148 to 883 ppm Slimicide C-68 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Slimicide C-68 per 1000 gallons of water in the system). Repeat until control is achieved.
SUBSEQUENT DOSE When microbial control is evident, add 35 to 219 ppm Slimicide C-68 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Slimicide C-68 per 1000 gallons of water) weekly or as needed to maintain control.
CONTINUOUS FEED METHOD
INITIAL DOSE When the system is noticeably fouled, apply 148 to 883 ppm Slimicide C-68 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of 5-micron C-68 per 1000 gallons of water in the system).
SUBSEQUENT DOSE Maintain this treatment level by adding a continuous feed of 35 to 219 ppm Slimicide C-68 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Slimicide C-68 per 1000 gallons of makeup water). Badly fouled systems must be cleaned before initial treatment.
NOTE For use only in industrial air washing systems that maintain effective mist eliminating components.



CORROSIVE LIQUID, N.O.S.
 See Proper Shipping Name
 UN 1168

RECEIVED

DEC 16 1982

Registration Division (TS-767)

ACCEPTED
 JAN 21 1983
 U.S. Environmental Protection Agency
 Washington, D.C. 20460
 Registered under
 EPA Reg. No. 3776-143

KEEP CONTAINER TIGHTLY CLOSED - PROTECT FROM FREEZING - STORE IN A DRY PLACE - DO NOT STORE AT ELEVATED TEMPERATURES
 BRTZ Laboratories, Inc. THE JOSEPH P. BERTZ COMPANY Tel. No. 215-955-8500