



OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

WASHINGTON, D.C. 20460

August 26, 2024

Coleen Gerber
coleen.gerber@veolia.com
VEOLIA WTS USA, INC.

Subject: Non-PRIA (Pesticide Registration Improvement Act) Labeling Amendment - Revisions to first aid statement, precautionary statements, company name, and storage and disposal information.
Product Name: SLIMICIDE C-68
Admin Number: 3876-143
EPA Receipt Date: 09/29/2023
Action Case Number: 00486788

Dear Coleen Gerber:

The amended labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable.

This approval does not affect any terms or conditions that were previously imposed on this registration. You continue to be subject to existing terms or conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one (1) copy of the final printed labeling before you release this product for shipment with the new labeling. In accordance with 40 CFR § 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR § 152.3.

Should you wish to add/retain a reference to your company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by EPA. If the website is false or misleading, the product will be considered to be misbranded and sale or distribution of the product is unlawful under FIFRA section 12(a)(1)(E). 40 CFR § 156.10(a)(5) lists examples of statements the EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the EPA find or if it is brought to our attention that a website contains statements or claims substantially differing from statements or claims made in connection with obtaining a FIFRA section 3 registration, the website will be referred to the EPA's Office of Enforcement and Compliance Assurance.

Your release for shipment of this product constitutes acceptance of these terms. If these terms are not complied with, this registration will be subject to cancellation in accordance with FIFRA section 6.

If you have questions, please contact Steven Snyderman via email at snyderman.steven@epa.gov.

Sincerely,

A handwritten signature in black ink that reads "Steven Snyderman". The script is elegant and cursive, with the first letters of "Steven" and "Snyderman" being capitalized and prominent.

Steven Snyderman, Product Manager, Team 33
RMB 2, AD
Office of Pesticide Programs

ACCEPTED

08/26/2024

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under

EPA Reg. No. 3876-143

SLIMICIDE C-68

INDUSTRIAL BIOCIDES FOR USE IN RECIRCULATING WATER COOLING
TOWERS AND AIR WASHER SYSTEMS**ACTIVE INGREDIENTS:**

5-Chloro-2-methyl-4-isothiazolin-3-one..... 1.11%

2-Methyl-4-isothiazolin-3-one.....0.39%

INERT INGREDIENTS:.....98.50%

TOTAL: 100.00%

CONTENTS: LIQUID

POUNDS PER GALLON: 8.6 (70°F)

EPA REGISTRATION NUMBER: 3876-143

EPA ESTABLISHMENT NUMBER: XXXX-XX-XX

KEEP OUT OF REACH OF CHILDREN**DANGER PELIGRO**[Note to Reviewer: In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed,
will appear on the front panel of the product label.]

FIRST AID	
If in eyes	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
If on skin or clothing	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
If swallowed	<ul style="list-style-type: none"> • Call a poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
If inhaled	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give

	artificial respiration, preferably by mouth-to-mouth, if possible. <ul style="list-style-type: none">• Call a poison control center or doctor for treatment advice.
HOT LINE Number: 1-800-877-1940	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-877-1940 for emergency medical treatment information.	
Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.	

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

Corrosive. Causes irreversible eye damage and skin burns. May be fatal if absorbed through skin. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Wear long-sleeve shirt, long pants, shoes with socks and chemical resistant apron. Wear rubber gloves, goggles and face shield when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS

This chemical is toxic to terrestrial and aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Apply this pesticide only as specified on this label.

PHYSICAL OR CHEMICAL HAZARDS

This product is corrosive to mild steel.

For Industrial Use. Technical advice regarding specific site problems is available from Veolia WTS USA, Inc.

A Material Safety Data Sheet containing more information relative to this product is available upon request.

For product use see Panel 2.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner that is inconsistent with its labeling.

Do not apply this product in a way that will contact workers or other persons.

INDUSTRIAL RECIRCULATING COOLING WATER SYSTEMS

This product aids in the control of bacteria, algae, and fungi in evaporative condensers, heat exchange water systems, commercial and industrial cooling towers, industrial water scrubbing systems, and brewery pasteurizers. Add this product to the tower basin, distribution box or some other point to insure uniform mixing. **BADLY FOULED SYSTEMS** must be cleaned before treatment is begun.

INITIAL DOSE: When the system is noticeably fouled, apply this product at the rate of 1.26 to 7.46 pounds (19 to 113 fluid ounces or 148 to 883 ppm) per 1000 gallons of water in the system. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add this product at the rate of 0.3 to 1.86 pounds (4.5 to 28 fluid ounces or 35 to 219 ppm) per 1,000 gallons in the system weekly or as needed to maintain control.

AIR WASHER SYSTEMS

For use only in industrial air washing systems that maintain effective mist eliminating components. To control bacteria, fungi, and algae which cause biofouling in industrial air washer systems, add this product to the air washer sump or chill water sump to insure uniform mixing, at the rate of 0.3 to 7.46 pounds (4.5 to 113 fluid ounces or 35 to 882 ppm) per 1,000 gallons of water in the system depending upon the severity of contamination. **BADLY FOULED SYSTEMS** must be cleaned before treatment is begun.

INTERMITTENT OR SLUG METHOD - INITIAL DOSE: When the system is noticeably fouled, apply this product at the rate of 1.26 to 7.46 pounds (19 to 113 fluid ounces or 148 to 883 ppm) per 1,000 gallons of water in the system. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add this product at the rate of 0.3 to 1.86 pounds (4.5 to 28 fluid ounces or 35 to 219 ppm) per 1,000 gallons of water in the system weekly or as needed to maintain control.

CONTINUOUS FEED METHOD – INITIAL DOSE: When the system is noticeably fouled, apply this product at the rate of 1.26 to 7.46 pounds (19 to 113 fluid ounces or 148 to 883 ppm) per 1,000 gallons of water in the system. **SUBSEQUENT DOSE:** Maintain this treatment level by adding a continuous feed of this product at the rate of 0.3 to 1.86 pounds (4.5 to 28 fluid ounces or 35 to 219 ppm) per 1,000 gallons of blowdown (or water loss) from the system.

METAL – WORKING FLUIDS

This product is recommended for the control of bacteria and fungi in soluble and emulsifiable-type aqueous metal-working fluids, such as emulsified petroleum oils, and formulations containing alcoholic fatty acid sulfonated red oil or naphthalene sulfonate. These fluids are usually prepared by diluting the product concentrates 1:40 to 1:60 with water.

For the maintenance of a non-fouled system, use this product at 32 fluid ounces per 1,000 gallons of emulsion (2 pounds) every 4 weeks or 32 to 154 fluid ounces per 1,000 gallons of emulsion (2 to 10 pounds) every 8 to 12 weeks. For a noticeably fouled system, use an initial dose of 64 to 154 fluid ounces per 1,000 gallons emulsion (4 to 10 pounds) to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. A higher dosage range and/or increased frequency of treatment may be required depending upon the rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed into the use-dilution of the metal-working fluid using a metering pump.

HYDRAULIC FLUIDS

This product is recommended as a preservative for use in the manufacture and use of high water-based hydraulic liquids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume of water in 60% by volume of mineral oil using an oil-soluble emulsifying agent.

For the maintenance of a non-fouled system, use this product at 110 to 135 fluid ounces (7.2 to 8.8 pounds) per 1000 gallons fluid every 8 weeks. For a noticeably fouled system, use an initial dose of 135 to 235 fluid ounces (8.8 to 15.4 pounds) per 1,000 gallons fluid to be followed by subsequent maintenance dosages. A higher dosage range and/or increased frequency of treatment may be required depending upon the rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

NON-POTABLE REVERSE OSMOSIS SYSTEMS

This product is recommended for the control of bacteria and fungi in non-potable reverse osmosis systems. Use of this product in potable water or dialysis is prohibited. Add 10 to 333 ppm of this product (0.15 to 5 ppm active ingredient) into reverse osmosis systems by either continuous feed or periodic injection. Compatibility of this product with reverse osmosis membranes should be confirmed with membrane manufacturers.

For the control of bacteria and fungi in carbon beds, add 10 to 333 ppm of this product (0.15 to 5 ppm active ingredient) by either continuous or batch feed. For periodic membrane cleaning, add 0.4 to 1.0 pound of this product to every 120 gallons of cleaning solution (6 to 15 ppm active ingredient). Badly fouled systems should be cleaned before treatment is begun.

PHOTOPROCESSING SYSTEMS

Start with a clean system. Water recycling: Use 2.1 to 4.2 pounds (32 to 64 fluid ounces) of this product per 1,000 gallons capacity of water in the system. Add to final rinse or used water collection tank by slug dose once weekly or as needed.

ONCE-THROUGH: Use 26 pounds (3 gallons) of product per 1,000 gallons capacity of water in the system, single application start-up dosage added to the wash tanks. Thereafter, add this product each operating day for one hour using a chemical proportioning pump at a dosage of 2 to 3 pounds per hour (32 to 48 fluid ounces) to wash tanks per 1,000 gallons of water used. Increase to two hours per day if needed.

The user is advised that he must maintain a level of discharge into the publicly owned treatment works which is in compliance with the recommended guidelines for the photographic processing industry. Contact your Regional EPA Office for guidance.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Keep container tightly closed when not in use. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous ~~and/or toxic~~. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING –

For metal and plastic containers less than or equal to 5 gallons: Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Triple Rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Pressure rinse as follows: Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip. Hold container upside down over application equipment or a mix tank or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the side of the container, and rinse at about 40 PSI for at least 30 seconds. Drain for 10 seconds after the flow begins to drip. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

For metal and plastic containers greater than 5 gallons: Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Recap and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Pressure rinse as follows: Empty the remaining contents into application equipment or a mix tank and continue to drain for 10 seconds after the flow begins to drip. Hold container upside down over application equipment or a mix tank or collect rinsate for later use or disposal. Insert pressure rinsing nozzle in the side of the container, and rinse at about 40 PSI for at least 30 seconds. Drain for 10 seconds after the flow begins to drip. Then offer for recycling or reconditioning if available or puncture and dispose of in a sanitary landfill, or incineration.

For fiber drums with liners: Nonrefillable container. Do not reuse or refill this container. Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then offer for recycling if available or dispose of in a sanitary landfill or by incineration. If drum is contaminated and cannot be reused, dispose of it in the manner required for its liner.

Veolia WTS USA, Inc.
3600 Horizon Boulevard
Trevose, PA 19053
Business Phone: 215-355-3300
Emergency Phone: 800-877-1940

{All text in brackets [xxx] is optional and may or may not be intended for final or market label.}
{All test in braces {xxx} is administrative and will not appear on a final or market label.}

[Lot] [Batch] Number:
Material ID:
Net Weight: _____
Packaging Date:
Made in:

{Optional Logos/Graphics}

