

Coppo

COPPER NAPHTHENATE

ACCEPTED
JPT - 11/14/71
44891-1

C O P P O

PRESERVATIVE FOR WOOD-CANVAS-ROPE

ARRÊST DECAY

This Ready-To-Use copper naphthenate complies with all requirements of Commercial Standard CS152-48, as developed by the trade in cooperation with the National Bureau of Standards of the U. S. Department of Commerce.

ANALYSIS

Active Ingredients	100%
Petroleum Distillate	90%
Copper Naphthenate	10%
(Copper as metal 1%)	

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE. KEEP OUT OF REACH OF CHILDREN. See back panel for additional cautions.

NET ONE GALLON

**CAUTION-COMBUSTIBLE MIXTURE
DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME**

N.Y.F.D.C. OF A. NO. 3597

WARNING! CONTAINS PETROLEUM DISTILLATE. HARMFUL OR FATAL IF SWALLOWED. SKIN AND EYE IRRITANT. VAPOR HARMFUL. DO NOT BREATHE VAPOR OR SPRAY MIST.

USE ONLY IN WELL VENTILATED AREA.

FIRST AID TREATMENT

IF SWALLOWED DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

IF SPLASHED INTO EYES—Immediately flush with water for at least 15 minutes. If irritation persists, get medical attention.

**KEEP CONTAINER CLOSED WHEN NOT IN USE
KEEP OUT OF REACH OF CHILDREN**

USE: An air-drying, copper-base preservative for wood, fabric and rope. Will arrest the action of decay, rot, fungi, termites and other wood infesting insects. Can be applied by dip, brush or spray, and will give long lasting protection. It has excellent penetrative properties, a high resistance to leaching (water insoluble), is long-lasting, and only a mild odor. The light green color is natural.

DIRECTIONS: Use as it comes from the package. Do not thin for dipping or spraying. Remove all previous paint coatings and cut away all rotten wood.

FOR BRUSH OR SPRAY: Apply liberally, using as many coats as necessary to secure penetration desired. Do not "skimp" or attempt to save material, because the degree of protection afforded is dependent upon the amount that penetrates into the structure of the wood. At least two flowing coats should be given by brush or flood spray application to all wood which is to come in contact with the ground.

FOR DIP: Length of time for soaking dependent upon thickness and type of wood. A minimum soaking time of 30 minutes suggested for thickness of 1" or less. Overnight soaking suggested in treating heavier timbers.

FOR CANVAS & ROPE: Apply so as to saturate thoroughly. Let dry before using.

SURFACES TO BE PAINTED LATER: If the treated surface is to be painted later, allow to dry 48 hours before painting. If white or light tints are used there might be a slight discoloration after first coat of paint is applied. This will disappear completely when second coat is applied, if wood is thoroughly dry.

COVERAGE: Varies by species and condition of wood. For general use, estimate 200 to 450 sq. ft. per gallon.

Klean-Strip

Division of W.M. Barr Inc. MEMPHIS TENNESSEE 38106



ACCEPTED
JUL 29 1977
4091-1