

**CAUTION - COMBUSTIBLE MIXTURE  
DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME**

N.Y.F.D.C. OF A. NO. 3597

**WARNING! CONTAINS PENTACHLOROPHENOL AND MIXED ALKANOLS AVERAGE C<sub>6</sub>. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. SKIN AND EYE IRRITANT. DO NOT BREATHE VAPOR OR SPRAY MIST. DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. USE ONLY IN WELL VENTILATED AREA. WASH THOROUGHLY AFTER HANDLING. KEEP PRESERVATIVE AND FRESHLY TREATED WOOD AWAY FROM FLAME, FOODSTUFFS AND PLANTS. DO NOT REUSE CONTAINER. DESTROY WHEN EMPTY.**

**WARNING! VAPORS WILL CAUSE INJURY IF ADEQUATE VENTILATION IS NOT INSURED. DO NOT USE THIS PRODUCT INDOORS OR ANY OTHER CONFINED AREAS WHERE THE VAPORS MAY CONCENTRATE AND CAUSE INJURY TO PLANT OR ANIMAL LIFE. WEAR RUBBER GLOVES AND PROTECTIVE CLOTHING WHEN HANDLING THE FRESHLY TREATED LUMBER.**

**FIRST AID TREATMENT**

**IF SWALLOWED INDUCE VOMITING BY ADMINISTERING EMETIC - CALL A PHYSICIAN IMMEDIATELY.**

**IF SPLASHED INTO EYES - Immediately flush with water for at least 15 minutes. If irritation persists, get medical attention.**

**FOR CONTACT WITH SKIN - Wash thoroughly with soap and water. If irritation persists, get medical attention.**

**KEEP CONTAINER CLOSED WHEN NOT IN USE  
KEEP OUT OF REACH OF CHILDREN**

**USE:** After recommended dilution this becomes a 5% penta wood preservative to stop rot and decay in unfinished wood . . . fenceposts, frames, sub floors, sills, joists, etc. Kills termites and other destructive wood boring insects. See side panels for additional information.

**DIRECTIONS: HOW TO MIX . . .** Dilute 1 part of this concentration with 10 parts by volume of a suitable petroleum solvent such as light fuel oil or paint thinner. Do not use without recommended dilution. **HOW TO APPLY . . .** All cutting should be completed before application. Wood must be clean, dry, and free from previous finishes. For best results wood should be completely immersed. An immersion period of 5 min. per inch of thickness is recommended. Liberal brush application or flood spray can be used if immersion is not practical.

**COVERAGE:** Varies by species and condition of wood. For general use of a 5% penta solution, estimate 150 to 200 sq. ft. per gal. for brush application, 5 to 10 gal. per thousand board feet for immersion treatment.

**SPECIAL NOTE:** We recommend Seal Treat where a water repellent, clear, and paintable penta wood preservative is desired.

**Klean-Strip**

DIV. OF W. M. BARR INC. MEMPHIS, TENN. 38111

