



BROOKS Chemicals

3304 EAST 87th STREET ACCEPTED CLEVELAND, OHIO 44127

Mar 12 1970 4297-16

H-C TREATMENT No. 475-P

U. S. D. A. Reg. No. 4297-16

For Slime and Algae Control

Net Contents

lbs.

DIRECTIONS FOR USE

Paper Mill Slime Control: Add to beaters 0.4 to 1.0 pound of No. 475-P per ton of paper produced.

Preservation of Sizes: For the preservation of paper sizes (cornstarch, dextrine, casein soya protein), use 0.1 to 1.0% of No. 475-P depending upon nature of size.

Slime and Algae Control in Cooling Water Systems: Clean system out before treatment and add a shock dose of two (2) pounds of 475-P per 2500 gallons of water in the system. Thereafter, add one (1) pound of 475-P per 3000 gallons of bleed-off per day. When control is attained, the dose may be dropped to one (1) pound of 475-P per 4000 gallons of bleed-off per day.

ACTIVE INGREDIENTS -----	90%
Sodium Pentachlorophenols -----	79%
Sodium Salts of other Chlorophenols -----	11%
INERT INGREDIENTS -----	10%

WARNING! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL DUST. CAUSES SKIN IRRITATION. ABSORBED THROUGH SKIN FROM SOLUTIONS.

Do not breathe dust. Do not get in eyes or skin, or on clothing. Do not take internally. Wash thoroughly after handling. In case of contact with dry material or its solution, wash skin at once with plenty of water for at least 15 minutes and get medical attention. Remove and wash clothing before reuse. If swallowed, induce vomiting. Call physician.

Note to Physician: This product is a metabolic stimulant, causes hyperthermia. Treat symptomatically.

This product is toxic to fish and wildlife. Do not dispose of treated effluent into fish-bearing waters. Apply this product only as specified on this label.

Do not reuse this container. Destroy when empty.

FOR INDUSTRIAL USE ONLY