

PACE PENTA

U. S. D. A. Reg. No. 4389-34

WATER REPELLENT WOOD PRESERVATIVE SOLUTION

For Wood That May Be Painted

INGREDIENTS

*Meeting Fed. Spec. TT-W-570

DIRECTIONS FOR USE

PACE PENTA water repellent solution is effective and economical for protecting wood from dry rot, mildew and fungi. The solution will also protect wood against swelling, warping and checking due to a too rapid change in moisture content.

Wood treated by brushing or spraying should receive two or more flowing coats of the product. For lumber intended to be in contact with the ground, a 14 day period of at least three coats is necessary. The solution is designed primarily for wood that is to be painted. When properly applied, the wood retains its natural appearance with a minimum of discoloration. If the wood is cut after applying PACE PENTA water repellent solution, the freshly cut surfaces should be treated to get the same protection.

NET CONTENT

WARNING:

INFLAMMABLE Contains volatile inflammable solvent. Do not pour, spill or spray near open flame and avoid breathing vapors.

CAUTION: KEEP OUT OF THE REACH OF CHILDREN.

HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. AVOID CONTACT WITH SKIN, EYES OR CLOTHING. IN CASE OF CONTACT WITH SKIN, EYES OR CLOTHING IMMEDIATELY WASH SKIN WITH SOAP AND PLENTY OF WARM WATER. FOR EYES, FLUSH WITH PLENTY OF WATER AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. REMOVE AND WASH CLOTHING BEFORE REUSE. DO NOT BREATHE SPRAY MIST.

This product has been formulated from material developed by present technical knowledge for this purpose. It should be used strictly as per directions.

PACIFIC CHEMICAL

