

NET CONTENTS
One U. S. Gallon

ACTIVE INGREDIENTS
Limonene 80.0%
Pine Tar Oil 15.0%
Pentachlorophenol 4.5%
Other Chlorinated Phenols .5%
TOTAL 100.0%

PENTA-PINE

WOOD PRESERVER

SEALS – PENETRATES – PROTECTS

Directions For Use

Penta-Pine can be applied to lumber, poles, post and other wood products by a hot and cold process, by soaking, spraying, or brushing, the most effective treatment is obtained where deep penetration and high absorptions result. Soaking or a hot-cold bath process gives better results than does spraying or brushing and should be used where possible. All wood must be air seasoned dry and barked before applying Penta-Pine. Allow to soak 24 to 48 hours. When wood is not in contact with the ground, brushing or spraying may be used. The joints should be thoroughly drenched. Penta-Pine is especially recommended for use against termites, wood rot fungus and moisture penetration. For protection against termites treat wood prior to use in construction. It may be painted over after allowing 48 hours to penetrate and dry. USDA Registration No. 4499-3.

– WARNING –

Keep Out Of The Reach Of Children:

HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

DO NOT BREATHE VAPOR OR SPRAY MIST.

DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.

WASH THOROUGHLY AFTER HANDLING.

DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

Manufactured and Packaged By

FLOYD PINE PRODUCTS COMPANY

ANDALUSIA, ALABAMA 36420, U. S. A.

