

OIL-PERGE

A BACTERIOSTAT FOR THE PRESERVATION OF OIL-IN-WATER METALWORKING CUTTING
FLUID EMULSIONS AND HYDRAULIC OIL EMULSIONS

ACTIVE INGREDIENT:

METHYLENE BIS(THIOCYANATE)..... 9.3%
INERT INGREDIENTS..... 90.7%

ACCEPTED
OCT 16 1964
UNDER THE FEDERAL
FUNGICIDE AND RODEN
FOR ECONOMIC POISON
ED UNDER NO. 464

DIRECTIONS FOR USE:

Metalworking Cutting Fluids: The recommended dosage to preserve oil-in-water metalworking cutting fluid emulsions is 2 fluid ounces of OIL-PERGE in 100 gallons of emulsion. Thoroughly mix the emulsion after addition of the OIL-PERGE by stirring or vigorous agitation to insure complete dispersion. The dosage should be repeated every two months or as needed to preserve the cutting fluid emulsion.

Emulsifiable Hydraulic Oils: When treating hydraulic oil emulsions used in hydraulic actuating systems, the recommended dosage is 2 fluid ounces of OIL-PERGE in 100 gallons of oil-in-water emulsions. The emulsion and OIL-PERGE should be thoroughly mixed together by stirring or vigorous agitation to insure complete dispersion. Repeat the dosage every two months or as needed to preserve the hydraulic oil emulsion.

DANGER: KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.

Corrosive. Causes eye damage and severe skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed or absorbed through skin. Avoid contamination of food. Do not breathe vapors.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For inhalation, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

This product is toxic to fish. Treated oil-in-water emulsions should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this product only as specified on the label.

Do not reuse empty drum. Rinse thoroughly with water and return to drum reconditioner, or destroy by perforating or crushing. Keep this product away from heat or open flames.

EPA Reg. No. 4643-26
EPA Est. No. 4643-IL-1

NET WEIGHT: 55 gallon drum - 485 lbs.
30 gallon drum - 265 lbs.



DEARBORN

OIL-PERGE

STABILIZER FOR THE PRESERVATION OF OIL-IN-WATER METALWORKING CUTTING
FLUID EMULSIONS AND HYDRAULIC OIL EMULSIONS

ACTIVE INGREDIENT:

METHYLENE BIS(THIOCYANATE)..... 9.3%
INERT INGREDIENTS..... 90.7%

The recommended dosage to preserve oil-in-water metalworking cutting fluid emulsions is 1 ounce of OIL-PERGE in 100 gallons of emulsion. Thoroughly mix the emulsion after addition of the OIL-PERGE with vigorous agitation to insure complete dispersion. The dosage should be repeated every two weeks to preserve the cutting fluid emulsion.

When treating hydraulic oil emulsions used in hydraulic actuating systems, the recommended dosage is 1 ounce of OIL-PERGE in 100 gallons of oil-in-water emulsions. The emulsion and OIL-PERGE should be mixed together by stirring or vigorous agitation to insure complete dispersion. Repeat the dosage as needed to preserve the hydraulic oil emulsion.

KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.

Avoid contact with eyes and severe skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles and gloves when handling. Harmful or fatal if swallowed or absorbed through skin. Avoid contact with and do not breathe vapors.

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For clothing, remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of water, gelatin solution or if these are not available, drink large quantities of water. Consult a physician immediately. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of epinephrine. Measures against circulatory shock, respiratory depression and convulsion may be needed.

Disposal: Treated oil-in-water emulsions should not be discharged where it will drain into public water. Do not contaminate water by cleaning of equipment or disposal of waste. See instructions specified on the label.

Store in a cool, dry place. Wash thoroughly with water and return to drum reconditioner, or destroy by perforating the drum and moving the product away from heat or open flames.

1-26
1-IL-1

NET WEIGHT: 55 gallon drum - 485 lbs.
30 gallon drum - 265 lbs.

ACCEPTED

OCT 16 1974

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
ED UNDER NO. 4643-26

1

DEARBORN CHEMICAL DIVISION

GENERAL ELECTRIC CORPORATION Lake Zurich, Ill. 60047