

DIRECTIONS

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Stir well before using.

Be sure surface is clean and dry. Apply generously by brush, roller or spray on new or bare wood, or previously finished surfaces. For best results, apply between 40° - 90°. Do not apply in hot sunlight. Two coats are usually enough on new wood or surfaces that are not badly weathered. If you want a higher sheen apply one or two coats of McCloskey Lumber Life Clear Gloss. For exterior furniture we recommend Lumber Life Patio Furniture Finish. Available in Redwood or Clear. For a clear finish and wood preservative use McCloskey Rott-Fyter.

CHECK FOR MILDEW

Lumber Life fights mildew after application. It will **not** kill mildew already there. Before staining check for mildew by applying a 50/50 solution of bleach and water. If washed area lightens mildew is present. Scrub all mildewed areas with a solution of 1 quart household bleach and 3 quarts of water. Let the solution work for 30 minutes, then rinse thoroughly with clear water. Allow the area to dry thoroughly before staining.

SPREADING RATE

200 to 400 square feet per gallon depending on the porosity of wood

DRYING TIME

Allow 6 to 8 hours before recoating. Drying time will vary with weather conditions, air circulation and temperature.

THINNING AGENT

Mineral spirits or paint thinner for thinning and clean-up.

WARNING:

Lumber Life Stain & Wood Preservative must be used in accordance with directions on this label to get satisfactory results, no warranty, expressed or implied is made. Buyers assume all risks when using the product contrary to directions on the label.

Note. Actual colors may vary from printed colors. A sample brush out on your wood type is recommended.

McCLOSKEY VARNISH CO.

Philadelphia 19136 — Los Angeles 90040

MADE IN U.S.A.

McCloskey Lumber Life Stain & Wood Preservative

Water-resistant for exterior siding, decking and fencing

High Hiding



ACORN BROWN 1301

FOR FULL DIRECTIONS ON
BACK OF LABEL

EPA REG. NO. 4

ONE GALLON (3.785 LITER)