EPA Form 8570-6 (Rev. 5-76)

PREV . JS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

91907: I: Pring le: P-1: KENCO: 9/2/87: 9/14/87: TG

# COASTAL LIQUID POOL SHOCK TREATMENT FOR SWIM POOLS

FOR CONTROL OF ALGAE AND SUPERCHLORINATION OF POOL WATER

# Active Ingredient:

Sodium Hypochlorite	12	.0%
Inert Ingredients	88 .	0%

## KEEP OUT OF REACH OF CHILDREN

DANGER: See Back Panel for Additional Precautionary and First Aid Statements.

NET CONTENTS: 1 gallon (3.785 liters)



# (BACK PANEL)

## DIRECTIONS FOR USE

Is is a violation of federal law to use this product in a manner inconsistent with its labeling.

Coastal Liquid Pool Shock Treatment was designed for ease of maintenance and control of algae growth. Simply add this instantly soluble liquid into your pool and the algae will begin to be destroyed.

For a new pool, spring start-up and on a weekly basis, superchlorinate pool water with  $5\frac{1}{2}$  to  $10\frac{1}{2}$  oz. of Liquid Pool Shock Treatment per 1,000 gallons of water to yield a 5-10 ppm available chlorine level. Pour liquid over a wide area of pool water surface to avoid bleaching of liner. Use a Coastal Test Kit to check available chlorine level. Indicate and maintain the pH of the pool water to between 7.2-7.6. Maintain the total alkalinity level between 50-100 ppm. Do not enter pool until chlorine residual falls to 1-3 ppm.

For swim pool maintenance, use 11 oz. of Liquid Pool Shock Treatment per 10,000 gallons of pool water to yield an available chlorine level of 0.6-1.0 ppm. Stabilized pools should maintain a residual of 1.0-1.5 ppm available chlorine. Test and adjust pH, chlorine residual and total alkalinity levels with a Coastal test kit. Treatment of swim pool water should be maintained with Iso Clor, Tarry or Tab-A-Day to insure proper chlorine residual.

At the end of the swimming pool season or when water is drained from the pool, allow chlorine level to dissipate from treated pool water before discharge. Do not chlorinate pool water 24 hours prior to discharge.

For winterizing use, add 3 oz. of Coastal Liquid Pool Shock Treatment per 1,000 gallons of water, while pool is still clean and clear. Run filter while adding Liquid Shock to ensure an even distribution. This treatment will provide an available chlorine residual of 3 ppm. Cover pool, prepare heater, filter, etc. in accordance with manufacturers instructions.

NOTE: This product degrades with age. Use a chlorine test kit ind', increase dosage, as necessary, to obtain the required level of available chlorine.

#### PRECAUTIONARY STATEMENTS

# HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, may cause severe skin and eye irritation or chemical burns to broken skin. Causes eye damage. Wear safety glasses or goggles and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until strong odors have dissipated.

BEST AVAILABLE COPY

### PHYSICAL OR CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (e.g. urine, feces, etc.) will release chlorine gas.

#### STATEMENT OF PRACTICAL TREATMENT

FIRST AID: IF CONTACT WITH EYES OCCURS, flush with water for at least 15 minutes. Get prompt medical attention. IF CONTACT WITH SKIN OCCURS, wash with plenty of soap and water. IF SWALLOWED, drink large quantities of milk or gelatin solution, if these are not available, drink large quantities of water. DO NOT give vinegar or other acids. DO NOT induce omiting. Get prompt medical attention.

#### ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not discharge into lakes, streams, ponds or public waterways unless in accordance with a NPDES permit. For guidance, contact the regional office of the EPA.

#### STORAGE AND DISPOSAL

Do not reuse empty container. Wrap container and put in trash.

EPA	REG.	NO.	EPA	EST.	NO.	4829-NJ-1

COASTAL CHEMICAL CO.
DIV. COASTAL INDUSTRIES INC.
CARLSTADT, N.J. 07072

