

KL-990® Super Epoxycop-TF

A high-performance, tin-free anti-fouling coating with excellent resistance to algae, barnacles and other marine fouling. Super Epoxycop-TF uses high levels of cuprous oxide in a tough epoxy coating to provide superior anti-fouling protection for all types of boats in fresh and salt water.

Directions for Use:

It is a violation of federal law to use or dispose of this product in a manner inconsistent with its labeling:

New fiberglass - No Sanding: Thoroughly clean with 551 Hi-Solvency Thinner & Cleaner, lifting the solvent, wax and contaminants off the surface with clean rags.

Apply one thin coat of 179 No Sanding Primer, allow to dry a minimum of one hour and a maximum of four hours, then apply two coats of KL-990 Super Epoxycop-TF by brush, roller or spray.

New Fiberglass - Epoxy Barrier Coat: Thoroughly clean with 551 Hi-Solvency Thinner & Cleaner, lifting the solvent, wax and contaminants off the surface with clean rags.

Abrade with 80 grit sandpaper, then seal with two coats of B370 Two-part Epoxy Primer. Sand between coats and before applying the anti-fouling coating (to improve adhesion). Apply two coats of KL-990 Super Epoxycop-TF by brush, roller or spray.

New Wood: Sand with 80 grit sandpaper, clean thoroughly and apply two coats of KL-990 Super Epoxycop-TF by brush, roller or spray.

Metal: Super Epoxycop-TF contains cuprous oxide and is not recommended for aluminum surfaces.

Iron and steel should be cleaned to bright metal and then sealed with two coats of anticorrosive primer such as B371 Red Lead Epoxy. Apply two coats of Super Epoxycop-TF by brush, roller or spray.

Previously Painted Surfaces: Hard epoxy and vinyl bottom paints that are in good condition can be abraded with 80 grit sandpaper and then over-coated with KL-990 Super Epoxycop-TF. Soft bottom paints and coatings that are cracked, damaged or peeling should be completely removed and the surface treated as if new.

Application Information

Mix thoroughly. Allow to dry at least overnight between coats and before launching. For best results, apply at least two coats. Apply by spray, short-nap roller or brush. Use 551 Hi-Solvency Thinner & Cleaner for thinning and cleaning equipment. Recommended application temperature range is 65°-80°F. Expected coverage is 350 to 400 square feet per gallon.

Maintenance

Physical damage, fuel spills and pollution can reduce the effectiveness of anti-fouling coatings. Therefore, it is recommended that the bottom be inspected periodically. Regular use or light scrubbing with a soft brush will help maintain a clean bottom.

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal. Store anti-fouling coatings in their original tightly-sealed containers.

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS

Hazardous to Humans and Domestic Animals

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Practical Treatment:

If Swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in Eyes: Flush with plenty of water. Get medical attention.

If On Skin: Wash with plenty of soap and water. Get medical attention.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This product is toxic to fish and other marine life. Do not apply directly to the water during cleaning or disposal of wastes. Do not allow chips or dust generated during paint removal to enter the water. Dispose of debris in an approved landfill.

Physical or Chemical Hazard


Do not use or store near heat or open flame.

E.P.A. Registration #7995-XX
E.P.A. Est. #7005-MA-1

Rule Industries, Inc.
Cape Ann Industrial Park
Gloucester, MA 01930, U.S.A.

*Rule Registered Trademark

BEST AVAILABLE COPY



MAY 1 1990

Coastal Industries
2265 Passaic Street
Passaic, N.J. 07055

BEST AVAILABLE COPY

Attention: Barbara A. Hoffmann

Product Name: Cal Jet Algaecide Liquid
Registration Number 4929-49
Application Date 2/7/90

The amendment referred to above, submitted in connection with registration under FIFRA, is acceptable provided that you:

1. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:

a. Delete "Ethanol" and "Sodium Carbonate" from the active ingredient, and include with the inert ingredients. Adjust inert percentages accordingly.

b. Revise referral statement on front panel to read:

"See back panel for additional Precautionary Statements".

c. Revise your Environmental Hazard statement to read:

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority.

59145:I:DeLaney:L-15:KENCO:4/30/90:5/27/90:dq:vo:ek:dq

CONCURRENCES

SYMBOL								
SURNAME								
DATE								


- d. In the ingredient section, delete "11.5%."
 - e. The statement "Active Ingredients" should be singular.
 - f. Revise the statement "To sanitize walls, runways locker rooms and other areas . . ." to read "To sanitize (non-food contact surfaces) walls, runways, locker rooms and other areas . . ."
 - g. Include a contact time for the sanitize (non-food contact surfaces) section.
2. Submit five (5) copies of your final printed labeling before you release the product for shipment.

Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha DeLaney at (703) 557-6982.

Sincerely yours,

John H. Lee 
 Product Manager (31)
 Antimicrobial Program Branch
 Registration Division (H7505C)

PM 31 4829-47

3044

CAL JET
Algaecide Liquid

ACTIVE INGREDIENTS.....	11.5%
Alkyl(60%Cl4, 25%Cl2, 15%Cl6) dimethyl benzyl ammonium chloride.....	7.5%
Ethanol.....	1.5%
Sodium carbonate.....	2.5%
INERT INGREDIENTS.....	88.5%
Total	100.0%

BEST AVAILABLE COPY

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAY 11 1990

KEEP OUT OF REACH OF CHILDREN
DANGER

DO NOT CONTAMINATE OR STORE NEAR FOOD OR FOOD-STUFFS. AVOID CONTACT WITH SKIN. DO NOT GET IN EYES. SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS AND STATEMENT OF PRACTICAL TREATMENT.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

NET CONTENTS: 1 QUART (32 fl. oz.) .946 l

CHEMICAL PROPERTIES

Coastal Cal Jet Algaecide Liquid is an outstanding algae growth depressant in all types and sizes of pools. It helps eliminate and prevent odors from confined water. Coastal Cal Jet Algaecide Liquid is fully compatible with alkalizing and flocculating agents normally used in swimming pools and is relatively non-corrosive to rubber and metals. It may be used with all types of equipment and works most effectively at pH levels over 7.0. Highly concentrated.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
Algae and slime may be effectively controlled with 1 gallon of Coastal Cal Jet Algaecide Liquid per 30,000 gallons of water. This is an initial treatment after the usual cleaning operation. For subsequent treatments, use 1 quart of Cal Jet Algaecide Liquid for each 30,000 gallons of water every 4 days. For initial treatment of small pools, use 1 pint to 4,000 gallons of water or 1 cup to 2,000 gallons. One cubic foot is about 7-1/2 gallons. In hot, sunny weather this dosage should be used every 2 days. Cal Jet Algaecide Liquid should be placed in the pool at various points or added through the filter. Each time the system is drained and refilled, repeat initial dose. To sanitize walls, runways, locker rooms and other areas surrounding swimming pool, apply with a clean mop or sponge, using a solution of 2 ounces of Cal Jet Algaecide Liquid in 4 gallons of water.

CAL JET ALGAECIDE LIQUID
USE CHART EVERY 4 DAYS

POOL SIZE	GALLON CAPACITY	DOSE VOLUME
8' x 20"	650	3/4 oz.
10' x 30"	1,475	1-3/4 oz.
12' x 36"	2,550	3 oz.
15' x 48"	5,300	6-1/4 oz.
18' x 48"	7,600	9 oz.
24' x 48"	13,500	15-3/4 oz.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

DANGER: Keep Out of Reach of Children. Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Protect eyes and skin when handling. Harmful if swallowed. Avoid contamination of food. Remove and wash contaminated clothing before reuse.

STATEMENT OF PRACTICAL TREATMENT

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes call a physician. If skin irritation persists, get medical attention. If swallowed, promptly drink large quantities of milk, egg whites, or gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance, contact your regional office of the E.P.A.

STORAGE AND DISPOSAL

Do not reuse empty container. Wrap and put in trash.

E.P.A. Reg. No. 4829-49

E.P.A. Est. No. 4829-VJ-1

Made & Printed in U.S.A.

COASTAL INDUSTRIES
225 Passaic Street
Passaic, NJ 07055

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAY 11 1990

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.