

MIXING DIRECTIONS

Mix Aldrin 4 lb. Emul. Conc. with water by agitation; agitate the mixture while spraying. If allowed to stand, reagitrate before use. This product can be used in conventional hydraulic sprayers and low-volume ground applicators.

CAUTION

WARNING!

Hazardous if swallowed, inhaled, or absorbed through skin! In case of contact, immediately remove contaminated clothing and flush skin or eyes with plenty of water. For eyes, get medical attention. Wash thoroughly with soap and water after handling and before eating or smoking; wear clean clothing. During commercial or prolonged exposure in spray-mixing and loading operations, wear clean synthetic rubber gloves and a mask or respirator of a type passed by the U. S. Dept. of Agriculture for Aldrin protection. Do not apply or allow to drift to areas occupied by unprotected humans or beneficial animals. To protect fish and wildlife, do not contaminate streams, lakes or ponds with this material. Do not contaminate food, utensils, dishes or drinking water. Do not apply to humans, pets or birds or near fish bowls. Keep out of reach of children. Use this product only for recommended purposes and at recommended dosages. **DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.**

USDA REG. NO. 4887-27

DILUTION CHART

Insect	Gals. 4 lb. Aldrin	Gals. Water
Termite (Use .5% solution or ratio 1 to 95)	1 qt.	23 1/2
	1 gal.	95

NOTICE: Since the use of this product is beyond the control of the seller, the seller makes no warranty of any kind, express or implied concerning the use or handling of this product. User assumes all risks of use or handling, whether in accordance with directions or not.

Contents _____ Gals.



ALDRIN

EMULSIFIABLE CONCENTRATE

FOR TERMITE CONTROL

WARNING!

KEEP OUT OF REACH OF CHILDREN

(SEE OTHER WARNINGS ON LABEL)

ACTIVE INGREDIENTS:

*Aldrin
 Petroleum Hydrocarbons

INERT INGREDIENTS:

*Equivalent to 40.7% Hexachlorocyclohexane-Endo, Exo-Dimethylnaphthalene and 2.2% related compounds. Contains 4 lbs. Aldrin per gal.

STEPHENSON CHEMICAL
 College Park, Md.

Aug. 16, 1966
 COMMENTS



ALDRIN 4 lb.

MULSIFIABLE CONCENTRATE FOR TERMITE CONTROL

WARNING

KEEP OUT OF REACH OF CHILDREN
(SEE OTHER WARNINGS ON SIDE PANEL)

INGREDIENTS:	
.....	42.9%
Petroleum Hydrocarbons	49.1%
INGREDIENTS:	8.0%
.....	100.0%

Equivalent to 40.7% Hexachlorocyclohexane-Endo, Deltamethane-naphthalene and 2.2% related compounds
in 4 lbs. Aldrin per gal.

STEPHENSON CHEMICAL CO., Inc.
College Park, Georgia

TERMITE CONTROL

SPECIFIC DIRECTIONS FOR COMMERCIAL OPERATORS

Use 0.5% solution of 4 lb. Aldrin E. C. as indicated on chart and apply at the following rates:

(A) Buildings with Crawl Spaces

- (1) Apply 2 gallons per 5 linear feet to critical areas only under the house, such as along the inside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in part (2) below.
- (2) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside those foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.
- (3) Apply 1 gallon per 10 square feet of soil surface under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the grade level. Where crawl spaces exist, treat as described in part (1) above.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gal. per 5 linear feet of wall. It is best to apply the chemical near the footing.

(B) Building with Concrete Slab on the Ground

- (1) Apply 1 gallon per 10 square feet as an over-all treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at grade level in case of washed gravel, cinders or similar coarse material, increase the dosage by at least one-half.
- (2) Apply 2 gallons per 5 linear feet to critical areas only under the slab, such as along the inside of foundation

walls, around sewer pipes, conduits, etc. Trench as in part (3) below.

- (3) Along the outside of foundation walls, dig a narrow trench no deeper than the top of the footings, but no deeper than 15 inches, unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A) (2).
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

(C) Building with Basements

- (1) Apply 1 gallon per 10 square feet as an over-all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.
- (2) Apply 2 gallons per 5 linear feet to critical areas only under the basement floorings, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in part (3) below.
- (3) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

3 4 5 6 7 8 9
Pesticides Registration
Division AHS
JUN 21 1966
RECEIVED

ACCEPTED
AUG 16 1966
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND REPLICANT ACT
FOR ECONOMIC PESTICIDES REGISTERED
UNDER NO. 287-27 SUBJECT
TO ATTACHED COMMENTS.

V

MIXING DIRECTIONS

Mix Aldrin 4 lb. Emul. Conc. with water by agitation; agitate the mixture when reagitated before use. This product can be used in conventional hydraulic sprayers and applicators.

CAUTION

WARNING!

Hazardous if swallowed, inhaled, or absorbed through skin! In case of contact, immediately remove contaminated clothing and flush skin or eyes with plenty of water. For eyes, get medical attention. Wash thoroughly with soap and water after handling and before eating or smoking; wear clean clothing. During commercial or prolonged exposure in spray-mixing and loading operations, wear clean synthetic rubber gloves and a mask or respirator of a type passed by the U. S. Dept. of Agriculture for Aldrin protection. Do not apply or allow to drift to areas occupied by unprotected humans or beneficial animals. To protect fish and wildlife, do not contaminate streams, lakes or ponds with this material. Do not contaminate food, utensils, dishes or drinking water. Do not apply to humans, pets or birds or near fish bowls. Keep out of reach of children. Use this product only for recommended purposes and at recommended dosages. **DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.**

USDA REG. NO. 4887-27

In
Termite
(Use .5%
ratio 1 to

NOTICE
yond the
no warra
concerni
duct. Us
ling, wh
or not.

ACCEPTED



ALDRIN 4 lb.

MULSIFIABLE CONCENTRATE FOR TERMITE CONTROL

WARNING

KEEP OUT OF REACH OF CHILDREN

(SEE OTHER WARNINGS ON SIDE PANEL)

INGREDIENTS:

.....	42.9%
Hydrocarbons	49.1%
INGREDIENTS:	8.0%
.....	100.0%

to 40.7% Hexachlorohexahydro-Endo,
nonaphthalene and 2.2% related compounds
lbs. Aldrin per gal.

STEPHENSON CHEMICAL CO., Inc.
College Park, Georgia

TERMITE CONTROL

SPECIFIC DIRECTIONS FOR COMMERCIAL OPERATORS

Use 0.5% solution of 4 lb. Aldrin E. C. as indicated on chart and apply at the following rate:

(A) Buildings with Crawl Spaces

- (1) Apply 2 gallons per 5 linear feet to critical areas only under the house, such as along the inside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in part (2) below.
- (2) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside those foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.
- (3) Apply 1 gallon per 10 square feet of soil surface under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the grade level. Where crawl spaces exist, treat as described in part (1) above.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

(B) Building with Concrete Slab on the Ground

- (1) Apply 1 gallon per 10 square feet as an over-all treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at grade level in case of washed gravel, cinders or similar coarse material, increase the dosage by at least one-half.
- (2) Apply 2 gallons per 5 linear feet to critical areas only under the slab, such as along the inside of foundation

walls, around sewer pipes, conduits, etc. Trench as in part (3) below.

- (3) Along the outside of foundation walls, dig a narrow trench no deeper than the top of the footings, but no deeper than 15 inches, unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A) (2).
- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

(C) Building with Basements

- (1) Apply 1 gallon per 10 square feet as an over-all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.
- (2) Apply 2 gallons per 5 linear feet to critical areas only under the basement floorings, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in part (3) below.
- (3) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.
- (4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

NS

re while spraying. If allowed to stand,
lic sprayers and low-volume ground ap-

DILUTION CHART

Insect	Gals. 4 lb. Aldrin	Gals. Water
mite e .5% solution or o 1 to 95)	1 qt.	23 $\frac{3}{4}$
	1 gal.	95

OTICE: Since the use of this product is be-
nd the control of the seller, the seller makes
warranty of any kind, express or implied
ncerning the use or handling of this pro-
ct. User assumes all risks of use or hand-
g, whether in accordance with directions
not.

Contents _____ Gals.



ALDRIN 4 lb.

EMULSIFIABLE CONCENTRATE

FOR TERMITE CONTROL

WARNING

KEEP OUT OF REACH OF CHILDREN

(SEE OTHER WARNINGS ON SIDE PANEL)

ACTIVE INGREDIENTS:

*Aldrin 42.9%
 Petroleum Hydrocarbons 49.1%

INERT INGREDIENTS: 8.0%
 100.0%

*Equivalent to 40.7% Hexachlorohexahydro-Endo,
 Exo-Dimethanonaphthalene and 2.2% related compounds
 Contains 4 lbs. Aldrin per gal.

TE SPECIFIC DIRECTION

Use 0.5% solution of 4 l
and apply at the following

(A) Buildings with Crawl

- (1) Apply 2 gallons p
under the house, :
walls, around pier
according to direct
- (2) Along the outside
trench, such trenc
the footings. If the
to the top of the
feet. Replace the
linear feet to the
thin layer of soil.
in depth to the top
linear feet. Replac
per 5 linear feet to
a thin layer of soi
mum depth requir
the top of the foot
lieu of trenching
15" deep and rod
foot apart.
- (3) Apply 1 gallon pe
attached porches,
and similar situat
level. Where craw
part (1) above.
- (4) Treat all voids in l
at the rate of at l

(B) Building with Concret

- (1) Apply 1 gallon pe
ment under the sl
entrance platform:
tions where slab
washed gravel, ci
crease the dosage
- (2) Apply 2 gallons p
under the slab, su

STEPHENSON CHEMICAL CO., Inc.
College Park, Georgia