

### DIRECTIONS

To make a 0.5 Emulsion, add 2½ gallons Heptachlor 2-E (2 lbs. actual Heptachlor per gallon) to 120 gallons water.

#### FOR TERMITES:

##### Slab-Type Construction

- Apply 1 gal. of 0.5% Emulsion per 10 square feet as an overall pre-construction treatment under the slab and along the attached porches or entrance platforms.
- Apply 2 gals. per 5 lineal feet to critical areas under slab as pre-construction treatment, such as along inside of foundation walls and around utility entrances and interior partition foundation walls.
- Apply 2 gallons per 5 lineal feet in a trench along the outside of foundation walls including entrance platforms and porches where the foundation is not more than 15-18 inches deep.

##### 2. Buildings with Crawl Spaces:

- Apply 5 gals. per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches but not over 30 inches, apply 4 gals. per 5 lineal feet. Do not go deeper than the top of the footing.
- Apply 2 gals. per 5 lineal feet as a trenching application to critical areas under the house, such as along the inside of foundation walls and around piers and utility entrances. If trench is deeper than 15-18 inches but not over 30 inches, apply 4 gals. per 5 lineal feet. Do not go deeper than the top of footing.
- Apply 1 gal. per 10 sq. feet of soil surface as a pre-construction treatment where the attached porches, entrance platforms, utility entrances, etc. have covering slab on fill of ground.
- Apply 1 gal. per 5 lineal feet of wall to voids in hollow masonry units of the foundation.

##### 3. Buildings with Basements:

- Apply 1 gal. per 10 square feet as an overall pre-construction treatment under the basement flooring, attached porches, entrance platforms, utility entrances etc. where slab fill is at ground level.
- Apply 2 gals. per 5 lineal feet in a trench along the outside of foundation walls, including entrance platforms and porches where the foundation is not more than 15-18 inches deep. If over 15-18 inches but not more than 30 inches apply 4 gals. per 5 lineal feet. Do not go deeper than top of the footing.
- Apply 2 gals. per 5 lineal feet as a trenching application to critical areas under the house, such as along the inside of foundation walls, porches, entrances and piers. If trench is deeper than 15-18 inches but not over 30 inches, apply 4 gallons per 5 lineal feet. Do not go deeper than top of footing.
- Treat all voids in hollow masonry units of foundation at the rate of 1 gal. per 5 lineal feet of foundation.

Premises treated with 0.5% Heptachlor will give residual control for a minimum of five years.

**CONTAINER DISPOSAL:** Do not re-use container. Destroy it by burying with waste or by burning. Stay away from smoke and fumes. This product is **TOXIC** to fish and wildlife. Birds feeding on treated areas may be killed. Keep out of any body of water. Do not apply when weather conditions favor drift from areas treated. Apply this product only as specified on this label.

**FLAMMABLE MIXTURE:** Keep away from heat or open flame.

# REDWOOD'S HEPTACHLOR 2E EMULSIFIABLE

(2 lbs. HEPTACHLOR per gallon)

#### Active Ingredients:

Heptachlor*	23.41%
Related Compounds	9.10%
Petroleum Distillate	61.36%
Inert Ingredients	6.13%
Total	100.00%

\*Heptachlorotetrahydro-4, 7-Methanoindene

**WARNING! Keep Out of Reach of Children. See Side Panel for Additional Cautions.**

**WARNING:** May be fatal if swallowed. Do not breathe vapor, dust or spray mist. Do not get on skin. In case of contact wash immediately with soap and water. Do not contaminate feed and foodstuffs. Keep out of reach of children.

**ANTIDOTE:** In case of spillage on skin, wash promptly with soap and water.

**Internal:** Emetic of 1 tablespoon mustard in glass of water. Call a physician.

Formulated By

**REDWOOD CHEMICAL INC.**

HOUSTON, TEXAS

Net Contents stamped USDA Reg. No. 4981-17

