

TRETOLITE

ACCEPTED

5009-4

MAY 20 1975

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGI-
STRATION NO. 5009-4

DIVISION

SAINT LOUIS, MISSOURI

X-CIDE® 320 Industrial Bactericide

FOR USE IN INDUSTRIAL PROCESSES ONLY. NOT FOR DOMESTIC USE. SEE DATA SHEET.
RECOMMENDED USE CONCENTRATION: 30-500 PPM OF X-CIDE, AS NEEDED.

EPA EST. 5009-CA 1; MO-1
EPA REG. NO. 5009-4

DANGER

**KEEP
OUT OF
REACH
OF
CHILDREN**

ACTIVE INGREDIENTS:

*Alkyl-1,3-propylene diamine acetates—	42.41%
*Alkyl=Octyl	8%
Decyl	9%
Dodecyl	47%
Tetradecyl	18%
Hexadecyl	8%
Octadecyl	5%
Octadecenyl	5%
Isopropyl mol	9.61%

INERT INGREDIENTS

	47.98%
Total	100.00%

DANGER — Keep Out of Reach of Children. Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID — In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

Do not use, pour, spill or store near heat or open flame.

This product is toxic to fish and birds. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

55 U.S. GAL. AT 60° F.

GROSS WT.

TRETOLITE DIVISION

XCIDE 505 is a highly effective product for use in controlling the growth of bacteria and fungi found in industrial recirculating water cooling towers, air washers, evaporative condensers, pulp mills, paper mills and cane sugar mills. XCIDE 505 is not recommended for potable water or where contamination of potable water can occur.

Active Ingredients

Sodium dimethyldithiocarbamate 15.
Nabam (Disodium ethylene bisdithiocarbamate) 15.

Inert Ingredients 70.0

ph $11.5 \pm 1.0\%$
Density $1.15 \pm 1.20\%$
Color Yellow green to green
Transmittance 95% minimum
Odor Hydrogen Sulfide
Weight per U.S. gallon 9.8 pounds
Storage Avoid extreme heat or freezing

HANDLING

XCIDE 505 causes eye and skin irritation. Do not get in eyes, on skin or clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed. Avoid contamination of food.

In case of contact, immediately flush eyes or skin with plenty of water for at least fifteen (15) minutes. For eyes call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are unavailable, drink large quantities of water. Call a physician immediately.

The following is a summary of dosage and feeding recommendations for each use of XCIDE 505.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS AND EVAPORATIVE CONDENSERS

Dosages for industrial recirculating water cooling towers or evapor-