

PETROLITE

728-7-888

ACCEPTED

SEP - 2 1988

Under the Federal Insecticide, Fungicide, and
Rodenticide Act, as amended, for the
pesticide registered under
EPA Reg. No. 5009-24

PETROLITE CORPORATION



PERFORMANCE-ENGINEERED PROGRAMS

PETROLITE INDUSTRIAL CHEMICALS GROUP

369 Marshall Ave. • St. Louis, MO 63119 • (314) 961-3500

Trademark of Petrolite Corporation

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: May be harmful or fatal if swallowed. Causes severe burns to eyes. May burn skin. Do not get in eyes, on skin, or on clothing. Wear goggles when handling. Wash thoroughly with soap and water after handling. Wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA.

FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

SPECTRUM™
2460

Industrial Microbiocide

FOR USE IN INDUSTRIAL PROCESSES ONLY, NOT FOR DOMESTIC USE.

ACTIVE INGREDIENTS:

2,2-Dibromo-3-nitrilo propionamide 20.0%

INERT INGREDIENTS: 80.0%

100.0%

KEEP OUT OF REACH OF CHILDREN
DANGER

SEE SIDE COLUMNS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA REG. NO. 5009-24

EPA EST. NO. 5009-MO-1; CA-1; TX-1

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.
INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

TREATMENT LEVELS: Bacterial growths in cooling water systems can be controlled by adding 0.12 to 1.2 fluid ounces SPECTRUM 2460/1000 gal. of water in the system (this is equivalent to 0.9 ppm to 8.0 ppm). The amount of SPECTRUM 2460 required will depend on the nature and extent of contamination, quality of the makeup water, and the degree of control required.

INTERMITTENT OR SLUG METHOD:

INITIAL DOSE: When the system is noticeably fouled, add 0.6 to 1.2 fluid oz. (4.5 ppm to 9 ppm) SPECTRUM 2460/1000 gal. of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.3 to 1.2 fluid oz. (2 ppm to 9 ppm) SPECTRUM 2460/1000 gal. of water in the system every 4 days, or as needed to maintain control. BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD:

INITIAL DOSE: When the system is noticeably fouled, add 0.6 to 1.2 fluid oz. (4.5 ppm to 9 ppm) SPECTRUM 2460/1000 gal. of water in the system. Subsequently, maintain this level by pumping a continuous feed of 0.5 to 5 fluid oz. (0.5 ppm to 5 ppm) SPECTRUM 2460/1000 gal. of water in the system lost by blowdown.

METHOD OF ADDITION: Feed the SPECTRUM 2460 with a metering pump directly into the basin. It can be added continuously or intermittently, as necessary to maintain control. Control should be based on visual inspection, microbiological analyses, and specific recommendations of the Petrolite Sales Engineer.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Do not use, pour, spill or store near heat or open flame.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess biocide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

55 U.S. GAL. AT 60°F.

GROSS WT.