



M-90[®] ALGAECIDE

ACTIVE INGREDIENTS

Sodium salt of 2,4,5 trichlorophenol	16.3%
Sodium salt of pentachlorophenol	3.4%
Sodium salts of other chlorophenols	0.5%
INERT INGREDIENTS	79.8%

(Includes Sodium Nitrate)

UOP M-90 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Badly fouled systems must be cleaned before treatment is begun. Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. An initial slug addition of 22.5-45.0 fluid ounces of the product per 1000 gallons of water (40-80 ppm of active ingredients based on total weight of water in system) is recommended. Subsequent slug additions of 11.25-22.5 fl. oz. of UOP M-90 per 1000 gallons of water (20-40 ppm of active ingredient) should be employed every 2 to 5 days or as needed. Apply at a point in the system where the product will be uniformly mixed. EPA Reg. No. 51.35-18.

Water Services Division
 Universal Oil Products Company
 700 South Flower Street • Burbank, California 91502



Water services



CAUTION: Keep Out of Reach of Children

Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Causes skin irritation. Harmful if swallowed. Do not breathe dust. Do not re-use empty container. Wash thoroughly with water and detergent. Discard in a safe place.

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Apply this product only as specified on this label.

ANTIDOTE

If M-90 comes in contact with skin, wash with soap and water. Do not continue to wear clothing soaked by M-90. If swallowed induce vomiting by giving a tablespoonful of salt in a glass of warm water and repeat until vomit fluid is clear. Apply artificial respiration if not breathing. **CALL PHYSICIAN.**

