

ACCEPTED

NOV 21 1980

5185-71

SC-125

ACTIVE INGREDIENT:

Potassium dimethyldithiocarbamate 12.5 %

INERT INGREDIENTS 87.5 %

This product contains 1.1 lb. of active ingredient per gallon and weighs 8.77 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN
DANGER

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Irritant. Causes skin irritation. Avoid contact with eyes. Wash thoroughly with water. Rinse eyes with water. Wash clothing. Remove and launder separately. Wash hands after handling.

STATEMENT OF PRACTICAL TREATMENT: In case of contact with skin, wash with plenty of water. Remove contaminated clothing and shoes. Wash thoroughly. For eye contact, flush with water for at least 15 minutes. If swallowed, drink plenty of water. Do not induce vomiting. If you experience any symptoms, call your physician.

ENVIRONMENTAL HAZARDS: This product is highly toxic to aquatic organisms. Do not apply near streams, rivers, lakes, or other bodies of water. Do not apply to lawns, gardens, or other areas where people or animals may be present. Do not apply to waterways or areas where waterfowl may be present.

Manufactured by:

EPA Reg. No.

EPA Est. No.

Net Contents

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SC-125 is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of SC-125 in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 9.5 to 14.2 fl. oz. of SC-125 per 1000 gal. of water to provide 80 to 120 ppm of SC-125 based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 4.7 to 14.2 fl. oz. of SC-125 per 1000 gal. of water (40 to 120 ppm) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

SC-125 is used in industrial air-washing systems which maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 22.2 to 28.4 fl. oz. of SC-125 per 1000 gal. of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.2 to 28.4 fl. oz. of SC-125 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection trays of the airwash system.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. STORAGE: Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or waste is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of your EPA Regional Office for guidance.

CONTAINER DISPOSAL: (1) PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. (2) METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.